

IGBT Module


Single switch

Short Circuit SOA Capability
Square RBSOA

$$I_{C80} = 600 \text{ A}$$

$$V_{CES} = 6500 \text{ V}$$

$$V_{CE(sat) \text{ typ}} = 4.2 \text{ V}$$



IGBT

Symbol	Conditions	Maximum Ratings
V_{CES}	$V_{GE} = 0 \text{ V}$	6500 V
V_{GES}		$\pm 20 \text{ V}$
I_{C85}	$T_C = 85^\circ\text{C}$	600 A
I_{CM}	$t_p = 1 \text{ ms}; T_C = 85^\circ\text{C}$	1200 A
t_{SC}	$V_{CC} = 4400 \text{ V}; V_{CEM \text{ CHIP}} \leq 6500 \text{ V};$ $V_{GE} \leq 15 \text{ V}; T_{VJ} \leq 125^\circ\text{C}$	10 μs

Symbol	Conditions	Characteristic Values ($T_{VJ} = 25^\circ\text{C}$, unless otherwise specified)		
		min.	typ.	max.
$V_{CE(sat)}^*$	$I_C = 600 \text{ A}; V_{GE} = 15 \text{ V}; T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$		4.2 5.4	V V
$V_{GE(th)}$	$I_C = 240 \text{ mA}; V_{CE} = V_{GE}$	6		8 V
I_{CES}	$V_{CE} = 6500 \text{ V}; V_{GE} = 0 \text{ V}; T_{VJ} = 125^\circ\text{C}$			120 mA
I_{GES}	$V_{CE} = 0 \text{ V}; V_{GE} = \pm 20 \text{ V}; T_{VJ} = 125^\circ\text{C}$			500 nA
$t_{d(on)}$	Inductive load; $T_{VJ} = 125^\circ\text{C};$ $V_{GE} = \pm 15 \text{ V}; V_{CC} = 3600 \text{ V};$ $I_C = 600 \text{ A}; L_\sigma = 280 \text{ nH}$	$R_G = 3.9 \Omega$	620	ns
t_r		$R_G = 3.9 \Omega$	270	ns
$t_{d(off)}$		$R_G = 2.7 \Omega$	1500	ns
t_f		$R_G = 2.7 \Omega$	930	ns
E_{on}		$R_G = 3.9 \Omega$	4250	mJ
E_{off}		$R_G = 2.7 \Omega$	3250	mJ
C_{ies}	$V_{CE} = 25 \text{ V}; V_{GE} = 0 \text{ V}; f = 1 \text{ MHz}$		150	nF
C_{oes}			7.57	nF
C_{res}			1.46	nF
Q_{ge}	$I_C = 600 \text{ A}; V_{CE} = 3600 \text{ V}; V_{GE} = \pm 15 \text{ V}$		9.65	μC
R_{thJC}				0.011 K/W

* Collector emitter saturation voltage is given at chip level

Features

- NPT³ IGBT
- Low-loss
- Smooth switching waveforms for good EMC
- Industry standard package
- High power density
- AISiC base-plate for high power cycling capacity
- AlN substrate for low thermal resistance

Typical Applications

- AC power converters for
 - industrial drives
 - windmills
 - traction
- LASER pulse generator

Diode







Symbol	Conditions	Maximum Ratings	
I_{F80}	$T_C = 80^\circ\text{C}$	600	A
I_{FSM}	$V_R = 0\text{ V}; T_{VJ} = 125^\circ\text{C}; t_p = 10\text{ ms}; \text{half-sinewave}$	6000	A

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
$V_F *$	$I_F = 600\text{ A}; T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = 125^\circ\text{C}$		3.2 3.4	V V
I_{RM}	$V_{CC} = 3600\text{ V}; I_C = 600\text{ A};$ $V_{GE} = \pm 15\text{ V}; R_G = 3.9\ \Omega; T_{VJ} = 125^\circ\text{C}$ Inductive load; $L_\sigma = 280\text{ nH}$		930	A
t_{rr}			2200	ns
Q_{RR}			1150	μC
E_{rec}			2100	mJ
R_{thJC}				0.021 K/W

* Forward voltage is given at chip level

Symbol	Conditions	Maximum Ratings	
T_{JM}	max junction temperature	+125	$^\circ\text{C}$
T_{VJ}	Operating temperature	-40...+125	$^\circ\text{C}$
T_{stg}	Storage temperature	-40...+125	$^\circ\text{C}$
V_{ISOL}	50 Hz, 1 min	10200	V~
M_d	Mounting torque		
	Base-heatsink, M6 screws	4 - 6	Nm
	Main terminals, M8 screws	8 - 10	Nm
	Auxiliary terminals, M4 screws	2 - 3	Nm

Symbol	Conditions	Characteristic Values		
		min.	typ.	max.
d_A	Clearance distance terminal to base	40		mm
	IEC 60664-1/EN 50124-1 terminal to terminal	26		mm
d_S	Surface creepage dist. terminal to base	64		mm
	IEC 60664-1/EN 50124-1 terminal to terminal	56		mm
V_E	Partial discharge extinction voltage $f = 50\text{ Hz}, Q_{PD} \leq 10\text{ pC}$ (IEC 61287)	5100		V
CTI	Comperative tracking index	600		
L_σ	Module stray inductance, C to E terminal		18	nH
$R_{term-chip} *$	Resistance terminal to chip		0.12	m Ω
R_{thCH}	per module; λ grease = 1 W/m $\cdot$ K		0.006	K/W
Weight			1760	g






Fig. 7 Typical switching energies per pulse versus collector current




Fig. 8 Typical switching energies per pulse versus gate resistor




Fig. 9 Typical switching times vs. collector current




Fig. 10 Typical switching times vs. gate resistor




Fig. 11 Turn-off safe operating area (RBSOA)




Fig. 12 Typ. diode forward characteristics, chip level

20110119a




Fig. 13 Typ. reverse recovery characteristics versus forward current




Fig. 14 Typ. reverse recovery characteristics versus di/dt




Fig. 15 Safe operating area diode (SOA)





Fig. 16 Thermal impedance vs. time

Outline drawing



$$Z_{th(j-c)}(t) = \sum_{i=1}^n R_i (1 - e^{-t/\tau_i})$$

	i	1	2
IGBT	R_i [K/kW]	8.5	2
	t_i [ms]	151	5.84
DIODE	R_i [K/kW]	17	4.2
	t_i [ms]	144	5.83