

"High Frequency Ceramic Solutions"

5.5 GHz Balun

Detail Specification: 10/23/12

P/N 5400BL15B100



Page 1 of 2

Part Number	Frequency (MHz)	Impedance Unbal. / Bal.	Insertion Loss	Return Loss	Phase Difference	Amplitude Difference
5400BL15B100_	4900 - 5875	50/100 Ω	1.0 dB max.	9.5 dB min.	180° $\pm$ 10°	2.0 dB max.

Input Power	Impedance	Operating Temperature Range	Reel Qty
3 Watts max	50 / 100 Ω	-40 to +85°C	4,000


Mechanical Dimensions

	L	W	T	a	b	c	g	p
Inches	0.079 $\pm$.004	0.049 $\pm$.004	0.037 $\pm$.004	0.012 $\pm$.004	0.008 $\pm$.004	0.012 $\pm$.004/-0.008	0.014 $\pm$.004	0.026 $\pm$.002
mm	2.0 $\pm$ 0.1	1.25 $\pm$ 0.1	0.95 $\pm$ 0.1	0.30 $\pm$ 0.1	0.20 $\pm$ 0.1	0.30 $\pm$ 0.1/-0.2	0.35 $\pm$ 0.1	0.65 $\pm$ 0.05



Terminal Configuration


1 Unbalanced Port	4 Balanced Port
2 GND or DC Feed	5 GND
3 Balanced Port	6 NC



Mounting Considerations

Mount devices with colored mark facing up.

Without DC feed




* Line width should be designed to provide 50 Ω impedance matching characteristics.

- Solder Resist
- Land
- Through-hole (ϕ 0.3)

Units: mm

With DC feed



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.

“High Frequency Ceramic Solutions”

5.5 GHz Balun

Detail Specification: 10/23/12

P/N 5400BL15B100

Page 2 of 2

