


Multilayer Ceramic Chip Capacitor

1812J6300103JGT

Knowles offers Multilayer Ceramic Chip Capacitors of the highest quality and reliability for a range of demanding applications. Manufactured using our "Wet Process", the range encompasses 10V to 12kV capability, with a variety of termination options including FlexiCap™, the worlds first commercially available flexible termination.



Mechanical Specification

Size Code	1812
Length (L1) mm	4.5 ± 0.3
Width (W) mm	3.2 ± 0.2
Thickness (H) mm	2.5 Max.
Termination Bands (L2,L3) mm	0.25 - 1.143
Minimum Band Gap (L4) mm	2.15
Termination Material	100% Matte Sn over Ni
Solderability	IEC 60068-2-58
RoHS Compliant	2011/65/EU as amended by 2015/863/EU
Packaging	Taped and Reeled, 7 inch Reel

General Electrical Specification

Rated Voltage	630V
Nominal Capacitance Value	10nF
Capacitance Tolerance	± 5%
Tangent of Loss Angle (Tan δ)	≤0.0015
Capacitance and Tan δ Test Conditions	1Vrms @ 1kHz
Voltage Proof	1.5 x Rated Voltage
(Voltage applied for 5 secs max. @ 50mA max. charge current)	
Min Insulation Resistance (IR)	100.00GΩ
Dielectric Classification	C0G (NP0)
Rated Temperature Range	-55°C to +125°C
Maximum Capacitance Change over Temperature Range	No DC Voltage 0±30ppm/°C
Climatic Category (IEC)	Rated DC Voltage -
Ageing Characteristic	55/125/56
	Zero

This datasheet is for a standard item and is confirmed valid on the date generated, the latest published data for this part may differ and is available at www.knowlesc capacitors.com/syfer or by contacting us at syfersales@knowles.com