



FEATURES

- Exclusive Laird Technologies gold-pated push-pin contact provides the most corrosion resistance and power transfer over time
- Long tuning ferrule allows for greater freedom in frequency adjustment without trimming
- Stainless steel corona ball stays on the rod - no dissimilar metal interaction associated with competitor designs

Model	Frequency	Color	Gain	Radiator
VHF Models				
AFT	118 - 896 MHz	Chrome	Unity	0.100" Dia. 1/4 Wave
ABFT	118 - 896 MHz	Black	Unity	0.100" Dia. 1/4 Wave
A150	150 - 174 MHz	Chrome	Unity	0.100" Dia. 1/4 Wave
A150S	150 - 174 MHz	Chrome	Unity	0.100" Dia. 1/4 Wave
AB150	150 - 174 MHz	Black	Unity	0.100" Dia. 1/4 Wave
UHF Models				
A450	450 - 470 MHz	Chrome	Unity	0.100" Dia. 1/4 Wave
AB450	450 - 470 MHz	Black	Unity	0.100" Dia. 1/4 Wave
A4503	450 - 470 MHz	Chrome	3.5 dBi	Open Collinear
A4503C	450 - 470 MHz	Chrome	3.5 dBi	Closed Collinear
AB4503	450 - 470 MHz	Black	3.5 dBi	Open Collinear
AB4503C	450 - 470 MHz	Black	3.5 dBi	Closed Collinear
700-800 MHz Antennas				
A7603	760 - 870 MHz	Chrome	3 dBi	Open Collinear
AB7603	760 - 870 MHz	Black	3 dBi	Open Collinear
A8063	806 - 896 MHz	Chrome	3 dBi	Open Collinear
A8963	896 - 970 MHz	Chrome	3 dBi	Open Collinear
A8063C	806 - 896 MHz	Chrome	3.5 dBi	Closed Collinear
A8065CT	806 - 896 MHz	Chrome	5 dBi	Closed Trilinear
AB8065CT	806 - 896 MHz	Black	5 dBi	Closed Trilinear
AB8063	806 - 896 MHz	Black	3 dBi	Open Collinear
AB8963	896 - 970 MHz	Black	3 dBi	Open Collinear
AB8063C	806 - 896 MHz	Black	3.5 dBi	Closed Collinear

global solutions: local support™

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com



Innovative **Technology**
for a **Connected** World

A-Base Antennas

Model	Frequency	Color	Gain	Radiator
800 MHz Models with Spring				
A8063S	806 - 896 MHz	Chrome	3 dBi	Open Collinear
A8063CS	806 - 896 MHz	Chrome	3.5 dBi	Closed Collinear
A8065CTS	806 - 896 MHz	Chrome	5 dBi	Closed Trilinear
AB8063S	806 - 896 MHz	Black	3 dBi	Open Collinear
AB8063CS	806 - 896 MHz	Black	3.5 dBi	Closed Collinear
AB8065CTS	806 - 896 MHz	Black	5 dBi	Closed Trilinear
2.4 GHz Models				
A2400	2400 - 2500 MHz	Chrome	Unity	
AB2400	2400 - 2500 MHz	Black	Unity	
A24003-OC	2400 - 2500 MHz	Chrome	3 dBi	Open Collinear
AB24003-OC	2400 - 2500 MHz	Black	3 dBi	Open Collinear
A24005-OT	2400 - 2500 MHz	Chrome	5 dBi	Open Trilinear
AB24005-OT	2400 - 2500 MHz	Black	5 dBi	Open Trilinear

ANT-DS-A-Base 0412

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2012 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.