



### LOW PROFILE SURFACE MOUNT 824-894/1710-2170 MHZ DISK ANTENNA

Laird's LPS82403NT antenna is a multiband low profile disk antenna operating over the 824-894 MHz and 1710-2170 MHz cellular bands. Designed to be a surface mount antenna that performs well on metallic and nonmetallic surfaces, the antenna is ideal for use in Machine-to-Machine (M2M) applications. The housing incorporates a low profile, rugged design that conforms to IP67 standards making the antenna suitable for both indoor and outdoor solutions.

### FEATURES

- Low Profile aesthetically neutral housing
- Surface mount with stud & locking nut
- Equitable for both Indoor & Outdoor applications
- IP67 rated

### BENEFITS

- Cellular and 2G/3G data communications in a single solution
- Applicable for both metal and non-metal housings

### MARKETS

- M2M
- Cellular
- Utilities, Remote Monitoring, Kiosks, ATMs
- Warehouse, Offices and Meeting rooms
- Hotels, Museums, Libraries, Retail Malls
- Airport, Bus Terminals and train Stations
- Other in-building areas



PARAMETER	SPECIFICATION	
Model Number	LPS82403NT-61SMAM	
Frequency	824-894 MHz	1710-2170 MHz
Gain (on Metal Housing)	2.39 (Max)	5.48 (Max)
Gain (on Plastic Housing)	1.86 (Max)	3.42 (Max)
Average Efficiency (on Metal Housing)	62%	68%
Average Efficiency (on Plastic Housing)	63%	64%
VSWR	< 3:1	
Max Input Power	10W	
Radiation Pattern	Omnidirectional	
Polarization	Linear	
Nominal Impedance	50 $\Omega$	
Antenna Dimension	26 (h) x 90 (dia.) mm (excludes gasket height)	
Weight	108.5 g (with SMA connector)	
Connector	SMA male or RPTNC male	
Coaxial Cable	RG316 (609.6 mm Length)	
Wind Survival	200 km/h	
Operational Temperature	-30°C to +70°C	
Storage Temperature	-40°C to +85°C	
Water/Foreign Body Ingress	IP67	
RoHS Compliance	Yes	

### CONNECTORS



MODEL NUMBER	CABLE LENGTH	CONNECTOR
LPS82403NT-61SMAM	610 mm (24 in)	SMA- male
LPS82403NT-61RTNM	610 mm (24 in)	RTNC- male

Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com  
Europe: +1.32.80.7866.12  
IAS-EUSales@lairdtech.com  
Asia: +1.65.6.243.8022  
IAS-AsiaSales@lairdtech.com



### AZIMUTH PATTERNS

### ELEVATION PATTERNS



**824 MHz Radiation Pattern**





**894 MHz Radiation Pattern**



**1710 MHz Radiation Pattern**



**2170 MHz Radiation Pattern**



ANT-DS-LPS82403NT 0913

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2013 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.