

Laird TechnologiesWeb site: www.LairdTech.com

All Categories > Squint™ Dual-Band Ceiling Mount Antenna > Phantom Antennas > Squint™ Directional Antennas for Horizontal Mounting Surfaces > Squint™ ISM Ceiling/Surface Mount Dipole Antenna > 2 dBi Omnidirectional Ceiling Mount Antenna for PCS > Cellular 4 dBi Gain Ceiling Mount Panel Antenna > Dual band 800 MHz/1900 MHz, 900 MHz/1700 MHz 4 dBi Ceiling Omnidirectional Antenna > SL8025WP Tri-Band Omni Antenna > SL80173WP Tri-Band Omni Antenna > 800 MHz Wall/Mast Mount Omnidirectional Antennas > 800/900 MHz. Omnidirectional Antennas for Data Communications > Laird Technologies Dual Feed, Linear & Circular Panel Antennas (CELL) > Item # S828HVP12NF

Item # S828HVP12NF, Dual Linear Antennas[larger image](#)**Linear Polarization Panel Antennas**

Laird Technologies linearly polarized panel antennas feature high performance and versatility. All antennas in the series are provided with UV stabilized radome enclosures and can be mounted to either interior or exterior wall surfaces or masts in either fixed or articulating configurations. Models are available from 8 dBi to 17 dBi gain. Integrated coaxial pigtails can be modified for length and connectors can be modified to suit the application. Consult your Laird Technologies Sales Representative to discuss these alternatives.

Dual Feed Panel Antennas

Dual feed panel antennas offer two ports for polarization diversity and are well suited to environments where multipath is a concern but space is limited. Polarization diversity allows the user to achieve the desired diversity benefit in the footprint of one antenna. All Laird Technologies dual feed antennas feature a minimum of 18 dB of port isolation.

HVP antennas offer diversity benefits in the foot print of a single antenna.

Circular Polarization Panel Antennas

Circular polarization antennas are a good choice for system applications where remote device orientation is random and widely variable.

Circular Polarized antennas mitigate performance degradation sometimes caused by variation in remote terminal orientation.

[Stock Locator](#)

Specifications

Frequency	824 to 896 MHz
Gain	8 dBi
VSWR	1.5:1
Polarization	Dual Linear Vertical & Horizontal
3dB Beamwidth, E Plane	65 °
3dB Beamwidth, H Plane	70 °

Weight	2.2 lbs 1.00 kg
RF Connector	N (Female)
Dimensions	12 x 12 x 1 3/4 in. 30.5 x 30.5 x 4.4 cm
Power	50 watts
Mounting Style	Surface Wall Mount

[Print](#)[Back](#)