

Laird TechnologiesWeb site: www.LairdTech.com

All Categories > Squint™ Dual-Band Ceiling Mount Antenna > Phantom Antennas > Squint™ Directional Antennas for Horizontal Mounting Surfaces > Squint™ ISM Ceiling/Surface Mount Dipole Antenna > 2 dBi Omnidirectional Ceiling Mount Antenna for PCS > Cellular 4 dBi Gain Ceiling Mount Panel Antenna > Dual band 800 MHz/1900 MHz, 900 MHz/1700 MHz 4 dBi Ceiling Omnidirectional Antenna > SL8025WP Tri-Band Omni Antenna > SL80173WP Tri-Band Omni Antenna > 800 MHz Wall/Mast Mount Omnidirectional Antennas > Item # S8802MP10NF


[larger image](#)
Item # S8802MP10NF, 800 MHz Wall/Mast Mount Omnidirectional Antennas
[Stock Locator](#)

Designed to provide a very attractive alternative, the antenna exhibits 2 dBi of omnidirectional gain in the AMP, GSM or SMR frequency band in a very diminutive package (antenna measures only 4" x 3" x 1.5"). For wall mounting, best omnidirectional coverage is achieved by mounting to an interior wall surface backed by traditional wood frame studs. Antenna comes standard with coax pigtail and N female, SMA or TNC connector.

Specifications

| | |
|-------------------------------|--------------------|
| Band | GSM AMP SMR |
| Frequency | 880 to 960 MHz |
| Gain | 2 dBi |
| 3dB Beamwidth, E Plane | 120 ° |
| 3dB Beamwidth, H Plane | 110 ° |
| VSWR | 2:1 |
| Polarization | Linear vertical |
| Weight | 0.4 lbs 0.18 kg |
| RF Connector | N (Female) |
| Enclosure Material | PVC |
| Power | 10 watts |
| Mounting Style | Yes |
| Dimensions | 4 x 3 x 1.5 in |

[Print](#) [Back](#)