

Vehicular 4-Port MIMO Antenna

VLQ24593xN4N



2400-2500 MHz / 4900-5925 MHz

The Laird vehicular 4-port MIMO Wi-Fi disk puck antenna covers the 2400-2500 MHz / 4900-5925 MHz bands. The VLQ24593xN4N is configured with 4-port, dual-band elements.

The four (4) WiFi ports have RP-SMA male cable plug connectors. The housing incorporates a low-profile, rugged design that meets IP67 standards. The antenna also features high impact, UV-resistant polycarbonate plastic available in black or white.

SPECIFICATIONS

PARAMETER	PERFORMANCE	
Model Number	VLQ24593BN4N-518B (Black)	VLQ24593WN4N-518B (White)
No. of Ports	4-ports (WiFi)	
Frequency Bands (MHz)	2400-2500 MHz	4900-5925 MHz
Peak Gain * dBi	2.2	3.5
Max Gain +/- 30° above horizon	N/A	3.5
VSWR** Typical	< 1.4:1	< 1.4:1
VSWR** Max	< 2.0:1	< 2.0:1
Typical Port-to-Port Isolation **	2400-2500 MHz	4900-5925 MHz
Port 1-to-Port 2	> 23 dB	> 28 dB
Port 1-to-Port 3	> 20 dB	> 26 dB
Port 1-to-Port 4	> 20 dB	> 26 dB
Port 2-to-Port 3	> 25 dB	> 26 dB
Port 2-to-Port 4	> 21 dB	> 26 dB
Port 3-to-Port 4	> 21 dB	> 28 dB
Port-to-Port Isolation **, Max	> 20 dB	> 26 dB
Nominal Impedance	50 Ω	
Polarization	Vertical Linear	
Azimuth Beam Width	Omnidirectional	
Input Power, Max	10 Watt per port (ambient temp. of 25°C / 77°F)	
Operating Temperature	-35°C to +75°C (-31°F to +167°F)	
Storage Temperature	-35°C to +80°C (-31°F to +176°F)	
Dimensions (dia. x hgt.)	127 mm x 38.5 mm (5.0" x 1.52")	
Weight	Approximately 0.91 kg (2.01 lbs)	
Connector	4 x RP-SMA-Male Cable Plug	
Cable (exposed length)	LMR195M- 518.2 cm (17 ft)	
Radome / Baseplate Material	PC, UL94 - V0 Rating, UV Stable	
Material Compliance	ROHS compliant	
IP Dust & Water Ingress Rating	IP67	

* Measured on 1 ft. (30.48 cm) diameter ground plane

** Measured with 17 ft. (518 cm) cable

PART NUMBERS

PART NUMBER		
VLQ24593BN4N-518B	4-Ports WiFi	4x RP-SMA Male (Black)
VLQ24593WN4N-518B	4-Ports WiFi	4x RP-SMA Male (White)

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com


www.lairdtech.com

Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective by reason of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.




RADIATION PATTERNS


2400 MHz




2440 MHz




2500 MHz




4900 MHz



5400 MHz



5925 MHz



ANT-DS-VLQ24593xN4N 0915

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.