


# AC4790-1X1

## 900MHz Radio Module



### THE FASTEST WAY TO WIRELESS

Laird Technologies' tiny AC4790-1x1 radio modules put the power of a pre-configured peer-to-peer protocol into the smallest, most cost-sensitive wireless applications. Despite their small size, 1x1 modules can communicate with any other in-range 1x1 radio module (even in harsh industrial conditions) allowing for virtually infinite range.

The AC4790-1x1's RF protocol features a dynamic addressing scheme that simplifies node-to-node communication. The radio module identifies the most efficient transmission path, so OEMs can design routing sequences that optimize the RF network. This makes 1x1 ideal for a wide variety of industrial applications that must rely on smooth, constant data flow.

Using field-proven 900MHz FHSS technology that utilizes unlicensed frequency bands\*, these modules reject interference, enable co-located system operation, and ensure data integrity. Integration is easy. OEMs simply solder the radio modules and antennas into place, then power-on. Hopping, synchronization, and data TX/RX is performed in the firmware.

### FEATURES

- True peer-to-peer protocol
- Ultra-fast sync time (25 msec)
- Smallest form factor: 1.0" x 1.0"
- API commands to control packet routing
- Software-adjustable sensitivity
- Network node discovery
- Range up to 1 mile

### MARKETS

- Commercial Buildings
- Field Surveillance
- Utility Management
- Recreation
- Fleet Telemetry

**global solutions: local support™**

USA: +1.800.492.2320

Europe: +44.1628.858.940

Asia: +852.2268.6567

wirelessinfo@lairdtech.com

[www.lairdtech.com/wireless](http://www.lairdtech.com/wireless)

### FLEXIBLE RF PROTOCOL

Laird Technologies' embedded transparent protocol simplifies the OEM's integration process by utilizing drop-in installation. As each radio module receives raw data, it manages the over-the-air protocol to assure successful communication. Headers, data packet length, and CRCs are not required. The RF232 supports simple cable-replacement to complex peer-to-peer configurations, broadcast communication to all radio modules or address packets to a specific destination using unique MAC addresses embedded in each radio module.

### SPECIFICATIONS

Parameter	AC4790-1x1
Interface	SMT
Frequency band (software selectable) (North America)**	902-928 MHz
Modulation	FHSS FSK
Serial interface options	3V TTL
Serial interface data rate	Up to 115.2 Kbps
Output power (w/ 3dBi antenna)	0mW-10mW variable
Current consumption (transmit/receive)†	80mA / 28mA
Channels	Up to 48 (North America)**
Security	One-byte system ID
Voltage	3.3V
Sensitivity	-99 dB @ full RF data rate
Range (line-of-sight w/ 3dBi antenna)	Up to 1 mile (1.6 km)
Temperature	-40° to +80°C
Humidity (non-condensing)	10% to 90%
Dimensions	1.0 x 1.0 x 0.2 inches (25.4 x 25.4 x 6.0 cm)
Weight	< 0.5 oz (< 15 g)
Antenna	External, via SMT pad


\*The 900MHz band is approved in the Americas and Australia as an unlicensed spectrum subject to approval by device.

\*\*For products and specifications suited to non-U.S. countries (e.g. Australia and Europe), please contact Laird Technologies.

†Current consumption assumes 50% transmitter on-time

The details contained within the document are subject to change. Download the product specification from [www.lairdtech.com/wireless](http://www.lairdtech.com/wireless) for the most current specification.

AC4790 1X1 is not FCC approved.  
Laird Technologies will assist with the approval process for high volume customers.



### RF PROTOCOL MODES

- Communication
  - Unicast (one-to-one addressing)
  - Broadcast (one-to-multiple addressing)
- Acknowledgement mode (ACK)
  - API with hardware and/or software ACK indication
- Ultra-fast sync time:
  - Up to 25 simultaneous conversations;
  - Intelligent self-extending session time requires only one 25 msec sync
- Remote over-the-air configuration
- Sensadjust, software-controlled RF desensitizer wards off interference
- Random back-off
- Network node discovery
- Dynamic radio data table:
  - Retains data from up to 8 radio modules

### INTERFACE PROTOCOL

- On-the-fly transceiver configuration:
  - Full API control
  - Destination address
  - RF transmit power
  - RF channel
  - Broadcast/addressed
- Raw data or transmit/receive API
- Long range mode, enables sensitivity control
- A/D, generic digital I/Os
- Variable baud rate
- RF packet size, timeout control
- Onboard temperature sensor
- Handshaking, CTS/RTS
- Session indicator
- Error detection
  - Onboard CR
  - Duplicate packet filtering
- Data encryption standard (DES)

LWS-SPEC-AC4790 1X1 0209

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request. For further information please visit our website at [www.lairdtech.com](http://www.lairdtech.com). Alternatively contact: [wirelessinfo@lairdtech.com](mailto:wirelessinfo@lairdtech.com). Bluetooth® is a trademark owned by Bluetooth SIG, Inc., USA and licensed to Laird Technologies.

© 2009 All Rights Reserved. Laird Technologies is a registered trademark of Laird Technologies, Inc.