




Part Number

FMW.5M.114.XLCT **Size/Series** 5MN / M **Request a quote**

MECHANICAL DETAILS

- Shell Style/Model** FM*: Straight plug with knurled grip and mold stop
- Keying** 5 keys (alpha= 95, beta=115, gamma=35, delta=25, plug: male contacts, receptacle: female contacts)
- Housing Material** Environment friendly aluminium (nickel plated, anthracite color) shell and nut, other pieces bronze/brass
- Cable Fixing** $\varnothing$: 0 - 0 mm
- Variant** :

	A	B	C	D	F	L	M	P	X
mm.	34.0	29.7	33.5	28.5	31.4	31.6	10.6	3.4	7.6
in.	1.34	1.17	1.32	1.12	1.24	1.24	0.42	0.13	0.30



PERFORMANCE DETAILS

- Insert Configuration** 5M.114 : 114 Low Voltage

OTHER CHARACTERISTICS

- Humidity (max):** <=95% [at 60 deg C /140 F]
- Vibration:** 15 g [10 Hz - 2000 Hz]
- Shock Resistance:** 100 g [6 ms]
- Operating temperature:** -55°C/ +200°C
- Climatical Category:** 15/200/21 (Al. shell)
- Lighting strike EIA 364-75** 10K amps - 6 times
- EMI Shielding EIA 364-66A** - 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB
- IP Rating** 50
- Catalog**

