


Part Number . . . **HEW.5M.114.XLNP**

Size/Series 5MN / M

[Request a quote](#)MECHANICAL DETAILS

Shell Style/Model	HE*: Fixed receptacle, nut fixing for printed circuit, watertight
Keying	5 keys (alpha= 95, beta=115, gamma=35, delta=25, plug: male contacts, receptacle: female contacts)
Housing Material	Environment friendly aluminium (nickel plated, anthracite color) shell and nut, other pieces bronze/brass
Cable Fixing	J : 0 - 0 mm
Variant	P : Watertight

	A	C	H	L	N	P	R	S1	S2	e
mm.	38.0	36.8	20.32	24.6	19.9	7.9	16.9	31.5	34.0	M33x1.00
in.	1.50	1.45	0.80	0.97	0.78	0.31	0.67	1.24	1.34	

PERFORMANCE DETAILS**Insert Configuration** 5M.114 : 114 Low VoltageOTHER CHARACTERISTICS

Humidity (max):	<=95% [at 60 deg C /140 F]
Vibration:	15 g [10 Hz - 2000 Hz]
Shock Resistance:	100 g [6 ms]
Operating temperature:	-55°C/ +200°C
Climatical Category:	15/200/21 (Al. shell)
Lighting strike EIA 364-75	10K amps - 6 times
EMI Shielding EIA 364-66A	- 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB
R leak (He) (max):	0.000001 mbar*Vs (if vacuum-tested)
IP Rating	50
Catalog	

[Copyright](#) [Privacy policy](#) [Product safety](#)