

8640 - Air Pressure Switches Series



Series:

Questions? [Contact Littelfuse Support](#)

For dependable operation of low air pressure warning systems.
Sealed contact design prevents short circuits caused by moisture and contaminants.
Normally On (Contacts open at rising pressure)
Mounting stem: 1/4" -18 dryseal thread.
Normally closed, open at 56 - 74 psi (386.1 – 510.2 kPa).
8-32 stud terminal.

Replaces Chrysler 1787025, 1788700, Delco 3750911, 3929518, Ford B6Q, B8Q-18737A, C5TZ-2A574A, International 194702-R91, Motorcraft SW-377.

 Feedback

Connect with Littelfuse

Sign up to receive special offers and news

For more details about how we use your information, check our [Privacy Statement](#).

Linked In Littelfuse Google Plus Facebook
Twitter Littelfuse YouTube Weibo RSS

 Mobile Site

About Littelfuse

About Littelfuse

Conflict Free Statement

History

Investor Relations

Legal

Press Room

Privacy Statement

Supply Chain Transparency

Website Feedback

Explore Littelfuse

Capabilities Brochures

Careers

Check Distributor Stock

Competitor Cross Reference

Industries

Order Samples

Products

Services

Technical Resources

Application Designs

Education

FAQs

iDesign™

Littelfuse University

Product Catalogs

Quality Documents

Technical Documents