Gas Discharge Tube (GDT) Products CG4 Series



RoHS

.....

CG4 Series



Agency Approvals

	AGENCY	AGENCY FILE NUMBER
FL E320116	711	E320116

Two Electrode GDT Graphical Symbol



Description

Littelfuse CG4 Gas Discharge Tubes (GDT) series provides high levels of protection against fast rising transients caused by lightning disturbances. Offered in a miniature surface mount package, it has a surge rating of 3kA 8/20µs.

Littelfuse CG4 mini GDTs are high voltage (800-3000V) devices designed for surge protection and high isolation applications. It is also suitable for applications for which bias voltage or signal levels of several hundred volts are normally present.

This CG4 mini GDTs are also suitable for applications with bias voltages or signal levels of several hundred volts. It can be used in conjunction with Littelfuse MOV (Metal Oxide Varistor) to provide superior protection performance.

Features

- Voltage Ranges 800V to 3000V
- Non-Radioactive
- Ultra Low capacitance
 Excellent response to fast rising transients
 BoHS compliant and
 - RoHS compliant and Lead-free
- 3kA 8/20µs surge rating
- UL 1449 recognized
- Offered with two squared terminals

Applications

- CATV equipment
- Antennas
- Air conditioning
- EV Power Station
- Inverters/Variable
 Frequency Drives (VFD)
- IEEE 803.2 compliant Ethernet interfaces
- Power Supplies
- Medical electronics
- Test Equipment
- Renewable Energy



Gas Discharge Tube (GDT) Products CG4 Series

Electrical Characteristics

	Device Specifications (at 25°C)						Life Ratings					
Part	DC	Breakdo in Volts (@100V/s)	own	Impulse Break- down in Volts (@100V/µs)	Impulse Break- down In Volts (@1 kV/µs)	Insulation Resistance	Capaci- tance (@1MHz)	Max Impulse Discharge Current (8/20µs)	AC Dischage Current (50Hz, 1sec)	AC Dischage Current (Single, 9 Cycles)	Arc Voltage (On State Voltage @ 1Amp, 1Min)	Impulse Life (10/1000µs) (100A)
Number	MIN	TYP	MAX	MAX		MIN	MAX		MIN	MIN		MIN
CG40.8	640	800	960	1200	1300	1GΩ*	0.8pf	10 Shots @ (3kA) 1 Shot at 5kA	ЗА	10A	20V	300 Shots
CG41.0	800	1000	1200	1400	1500							
CG41.2	960	1200	1440	1600	1700							
CG41.8	1440	1800	2160	2400	2500							
CG42.0	1600	2000	2400	2600	2700							
CG42.5	2000	2500	3000	3000	3200							
CG42.7	2160	2700	3240	3200	3600							
CG43.0	2400	3000	3600	3500	3900	1						

Note:

* Insulation resistance measured at:

250Vdc for CG40.8,

 \bullet 500Vdc for CG41.0 8, CG41.0, CG41.8 and CG42.0,

 \bullet 1000Vdc for CG42.5, CG42.7 and CG43.0

Product Characteristics

Materials	Device Tin Plated 17.5 ± 12.5 Microns Construction: Ceramic Insulator
Storage and Operational Temperature	-40 to +90°C

Soldering Parameters - Reflow Soldering (Surface Mount Devices)

Reflow Co	ndition	Pb – Free assembly		
	-Temperature Min (T _{s(min)})	150°C		
Pre Heat	-Temperature Max (T _{s(max)})	200°C		
	-Time (Min to Max) (t _s)	60 – 180 secs		
Average ra (T _L) to pea	amp up rate (LiquidusTemp k	3°C/second max		
$T_{S(max)}$ to T_L	- Ramp-up Rate	5°C/second max		
Poflow	-Temperature (T _L) (Liquidus)	217°C		
nellow	-Temperature (t _L)	60 – 150 seconds		
PeakTemp	erature (T _P)	260 ^{+0/-5} °C		
Time with Temperatu	in 5°C of actual peak ıre (t _p)	10 – 30 seconds		
Ramp-dov	vn Rate	6°C/second max		
Time 25°C	to peakTemperature (T _P)	8 minutes Max.		
Do not exc	ceed	260°C		



Gas Discharge Tube (GDT) Products CG4 Series



Device Dimensions

Dimensions in millimeters



Product Marking



Part Numbering System and Ordering Information



SM (Surface Mount, two squared terminals)

Taping and Reel Specifications

A0

Unit = mm Item Spec Item Spec Ρ Е 8 ± 0.1 1.75 ± 0.1 P0 4.0 ± 0.1 D $\emptyset 1.55 \pm 0.05$ W 16.0 ± 0.3 Κ 6.5 ± 0.1 F 7.5 ± 0.1 t 0.4 ± 0.05

B0



Packaging Quantity:

 4.9 ± 0.1

1000 pcs per reel (13")1 reels per inner box10 inners box per carton10,000 pcs per full carton

 6.5 ± 0.1

