



MLS

MLS - ideal as task lighting for use in medical facilities. A 8.125 in. (206 mm) diameter shade with inner reflector and 5-ring louver eliminates glare and protects the bulb from accidental touch or breakage. Heavy duty, 20-gauge, CRS K-arm with 0.5 in. (13 mm) square tubing and internal tempered steel springs assures proper balance and ease of movement while providing optimal durability.



- 8.125 in. (206 mm) diameter shade with inner reflector
- 5-ring louver
- Heavy-duty, 20-gauge, CRS K-arm
- UL/CUL Listed
- Mounting options sold separately
- Color: Light Grey

RELATED PRODUCTS

MLC



MLY

CODES

MLS100 - 5FT. CORD LENGTH

Article Number	Light Source	Watt	Weight	Arm Length	Mount	Ctn. Colors
14210LG	Incandescent 100W	4.4	45.0/1143	Wall mount	1	■

MLS100H - HARDWIRED

Article Number	Light Source	Watt	Weight	Arm Length	Mount	Ctn. Colors
14212LG	Incandescent 100W	4.4	45.0/1143	Wall mount	1	■

MLS100S - 18IN. CORD LENGTH

Article Number	Light Source	Watt	Weight	Arm Length	Mount	Ctn. Colors
14211LG	Incandescent 100W	4.4	45.0/1143	Wall mount	1	■

MLS145 - 5FT. CORD LENGTH

Article Number	Light Source	Watt	Weight	Arm Length	Mount	Ctn. Colors
14215LG	Incandescent 100W	4.4	45.0/1143	Edge/Floor stand	1	■

MLS150 - 5FT. CORD LENGTH

Article Number	Light Source	Watt	Weight	Arm Length	Mount	Ctn. Colors
14220LG	Incandescent 100W	4.4	50.0/1270	Wall mount	1	■

MLS150S - 13 IN. CORD LENGTH

Article Number	Light Source	Watt	Weight	Arm Length	Mount	Ctn. Colors
14221LG	Incandescent 100W	4.4	50.0/1270	Wall mount	1	■

ACCESSORIES

34" Floor Stand	50036
Wall Bracket	50003
Wall Bracket	50003
Edge Clamp	60001
Louver/5-Ring	31627
MLS, MLY Surface Mount	50026LG
Double Gang Box Mount	50024LG

DESIGNATION