

# Circus CIR025725

### CIR T100WH 122 840 5D CLA NA

Circus is specially designed to withstand the rigors of everyday use in industrial and manufacturing environments as well as cosmetology, health spas, beauty salons and clean room applications where FOD is a concern. No knobs to tighten, nothing to adjust. A 5-diopter white **Oldvitemenoulally 981** Werbs provides distortion-free viewing. The highly- flexible, self-balancing shade and 45" internal spring arm allows



Electrical data	
Maximum frequency (Hz)	6 0
Minimum frequency (Hz)	5 0
Maximum voltage (V)	120
Voltage from (V)	100
Total consumption (W)	2 3
Optic	
Primary Lens (D)	5
Working distance (mm)	200
Magnification (X)	2.25
Dimensions	
Net weight (kg)	5,69
Arm length (in.)	3 9



Lightsource	
Number of lamps	1
Lamp power (W)	2 2
Lamp base	2GX13
Lightsource	Fluorescent circular T5-C
Technical data	
Maximum ambient temperature (°C)	2 5
IP classification	2 0
Termination	
Plug type	N A
Cord length (ft)	6
Body	
Body color	Grey



# Circus CIR025725

#### CIR T100WH 122 840 5D CLA NA

Circus is specially designed to withstand the rigors of everyday use in industrial and manufacturing environments as well as cosmetology, health spas, beauty salons and clean room applications where FOD is a













## Circus CIR025725

### CIR T100WH 122 840 5D CLA NA

Circus is specially designed to withstand the rigors of everyday use in industrial and manufacturing environments as well as cosmetology, health spas, beauty salons and clean room applications where FOD is a concern. No knobs to tighten, nothing to adjust. A 5-diopter white crown optical-quality glass lens provides distortion-free viewing. The





### Drawings

