

## WAVE LED UV

## WAL026780

Old item no.:



## WaveLED-UV T105BI3,5DCLA ESDNA

Wave LED UV-ESD is an illuminated magnifier designed for the inspection of conformal coatings in static-sensitive environments where electrostatic discharges can prove fatal for electronic components. The shade and arm are powder-coated with a metal-laced paint that measures  $10^4 \Omega/\text{sq.}$  (conductive). The remaining components are molded in a material that measures  $10^5 - 10^6 \Omega/\text{sq.}$  (static dissipative). Since the surfaces are no longer insulative, triboelectric charging results in drastically lower voltages, especially since any charge (under 50 volts) is uniformly distributed throughout the entire surface of the head assembly. No knobs to tighten, nothing to adjust - a flexible, self-balancing shade and hands-free neck assembly combined with 45" heavy-duty internal-spring parallel, three-pivot K-arm, allows the lamp head to be secured in any position. The fully-enclosed neck

## Lightsource

Number of lamps	2
Lightsource	LED
CRI and/or Color Temperature	80 CRI, 4000K
Lamp power (W)	12
Lumen/Watt	46
Lumen Out	600
LLMF LED 50000h Ta25	0.80

## Technical data

Maximum ambient temperature (°C)	25
IP classification	20
ESD-Safe	Yes

## Termination

Plug type	NA
Cord length (ft)	1.7
Mounting	Edge clamp



## Electrical data

Voltage from (V)	230
Maximum voltage (V)	240
Maximum frequency (Hz)	60
Minimum frequency (Hz)	50
Total consumption (W)	13

## Optic

Primary Lens (D)	3.5
Working distance (mm)	285.7
Magnification (X)	1.88

## Dimensions

Net weight (kg)	3.5
Arm length (in.)	45

## Body

Body color	Black
------------	-------

## WAVE LED UV WAL026780



### WaveLED-UV T105BI3,5DCLA ESDNA

Wave LED UV-ESD is an illuminated magnifier designed for the inspection of conformal coatings in static-sensitive environments where electrostatic discharges can prove fatal for electronic components. The



## Photos




# WAVE LED UV WAL026780



## WaveLED-UV T105BI3,5DCLA ESDNA

Wave LED UV-ESD is an illuminated magnifier designed for the inspection of conformal coatings in static-sensitive environments where electrostatic discharges can prove fatal for electronic components. The shade and arm are powder-coated with a metal-laced paint that measures  $10^4\Omega/\text{sq.}$  (conductive). The remaining components are made of material that measures  $10^5 - 10^6\Omega/\text{sq.}$  (static)



## Drawings

