



Silicon Switching Diode Series

1N914UR & 1N4148UR-1

Features

- Available in JAN, JANTX, and JANTXV per MIL-PRF-19500/116
- Metallurgically Bonded
- Hermetically Sealed
- Double Plug Construction

Maximum Ratings

Operating & Storage Temperature: -65°C to +175°C

Surge Current A, sine 8.3ms: 2.0 A

Surge Current B, square 8.3ms: 0.704 A

Operating Current: 125mA, $T_A = +75^\circ\text{C}$

Derating Factor: 2.0 mA/°C above $T_A = +25^\circ\text{C}$

D.C. Reverse Voltage (VRWM): 75V




Electrical Specifications @ +25 °C (Unless Otherwise Specified)

JEDEC TYPE Number	V_{BR} @ 100 μA	V_{RWM}	I_O	V_{f1} $I_F = 10 \text{ mA}$	V_{f2} $I_F = 50 \text{ mA}$	T_{rr} (Note 1)	I_{R1} @ 20 Vdc	I_{R2} @ 75 Vdc	I_{R3} @ 20 Vdc $T_A = 150^\circ\text{C}$	I_{R4} @ 75 Vdc $T_A = 150^\circ\text{C}$	Capacitance @ 0V	Capacitance @ 1.5 V
	Volts	Volts (pk)	mA	Vdc	Vdc	nsec	nA	μA	μA	μA	pF	PF
1N914UR	100	75	75	0.8	1.2	5	25	0.5	35	75	4.0	2.8
1N4148UR-1	100	75	200	0.8	1.2	5	35	0.5	35	75	4.0	2.8

Note1: $I_F = I_R = 10 \text{ mA}$, $R_L = 100 \text{ ohms}$.

Outline Drawing



LEADED DESIGN DATA

CASE: DO-213AA, Hermetically sealed glass case. (MELF, SOD-80, LL34)

LEAD FINISH: Tin / Lead


THERMAL RESISTANCE: ($R_{\theta JEC}$): 100 °C/W maximum at L = 0 inch

THERMAL IMPEDANCE: ($Z_{\theta JX}$): 25 °C/W maximum

POLARITY: Diode to be operated with the banded (cathode) end positive.


MOUNTING POSITION: Any.

Graphs



Typical Forward Current
vs Forward Voltage

NOTE : All temperatures shown on graphs are junction temperatures



Typical Reverse Current
vs Reverse Voltage

Aeroflex / Metelics, Inc.

975 Stewart Drive,
Sunnyvale, CA 94085
Tel: (408) 737-8181
Fax: (408) 733-7645

Sales: 888-641-SEMI (7364)

Hi-Rel Components
9 Hampshire Street,
Lawrence, MA 01840
Tel: (603) 641-3800
Fax: (978) 683-3264

www.aeroflex.com/metelics-hirelcomponents

54 Grenier Field Road,
Londonderry, NH 03053
Tel: (603) 641-3800
Fax: (603)-641-3500

ISO 9001: 2008 certified companies

www.aeroflex.com/metelics metelics-sales@aeroflex.com

Aeroflex / Metelics, Inc. reserves the right to make changes to any products and services herein at any time without notice. Consult Aeroflex or an authorized sales representative to verify that the information in this data sheet is current before using this product. Aeroflex does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by Aeroflex; nor does the purchase, lease, or use of a product or service from Aeroflex convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of Aeroflex or of third parties.

Copyright 2009 Aeroflex / Metelics. All rights reserved.



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.