



[[Home](#)] [[View Cart](#)] [[Site Map](#)] [[Contact](#)] [[Legal](#)]

OCDemon™ from Macraigor Systems

Make your debugging a little bit easier ...



[[Home](#)] [[Hardware Products](#)] [[Software Products](#)] [[CPUs](#)] [[Tools, etc.](#)] [[FAQ](#)] [[Partners](#)] [[News](#)]

Wiggler

Raven

usb2Demon™

USBWIGGLER™

usb2Sprite™

mpDemon™

Adapters

usbWiggler™...

Connects to USB 1.1 and USB 2 (Hi-Speed) systems ...

The **usbWiggler™** is a **Universal Serial Bus interface for JTAG and BDM debugging**. Faster than the classic parallel port Wiggler, it is a stable, easy to use device and is fully compatible with all of our software. In addition, it is a true **USB 2.0 high speed device**.

Note that the usbWiggler can be upgraded later to the clock speeds of a usb2Demon.

The usbWiggler™ is a mid-cost interface used in the design, debug, and programming of microprocessor based embedded systems. One side of the usbWiggler interfaces to the USB port of a host IBM compatible PC and the other side connects to an OCD (On-Chip Debug) port of the target system. This port may be JTAG, E-JTAG, OnCE, COP, BDM or any of several other types of connections. When connected to a USB 2.0 port on your PC, the usbWiggler will operate up to Hi-Speed USB rates (480Mb/s). 32-bit Windows platforms only at this time.

MAKE SURE WE SUPPORT YOUR TARGET PROCESSOR. [CLICK HERE!](#)

NOW SUPPORTED UNDER LINUX.

Sample download speeds in Bytes per second:

ARM7: 43,000

ARM9: 49,000

AU1xx0: 12,000

MPC82xx: 20,000

MPC85xx: 144,000

PPC440: 39,000

XScale: 119,000

\$250.00

PURCHASE