Solutions

ENGLISH • 简体中文 • 日本語 • 한국어

Login | Register



**Products** 

Enter keywords or part number

Sales | About Us | Members |

Maxim > Products > [Storage Products (SAS/SATA/Enclosure Management)] [Optoelectronics]

Design

# MAX3678EVKIT

Support

**AppNotes** 

Evaluation Kit for the MAX3678

QuickView Technical Documents Ordering Info More Information User Comments (0) All

**Status** 

What's New

Active: In Production.

### Description

The MAX3678 evaluation kit (EV kit) is a fully assembled and tested demonstration board that simplifies evaluation of the MAX3678 low-jitter frequency synthesizer with intelligent dynamic switching (IDS). The EV kit includes slide switches to allow easy selection of different modes of operation. Clock I/Os have SMA connectors and are AC-coupled to simplify connection to test equipm

Request Full Data Sheet

operation. Clock I/Os have SMA connectors and are AC-coupled to simplify connection to test equipment. The EV kit is powered by a +3.3V supply and uses LEDs for signal status indicators.

### **Key Features**

- Fully Assembled and Tested
- Slide Switches for Mode Control
- SMA Connectors and AC-Coupled Clock I/Os
- Powered by +3.3V Supply
- LED Signal Status Indicators

# Didn't Find What You Need?

- Next Day Product Selection Assistance from Applications Engineers
- Parametric Search
- Applications Help

# QuickView

Description Key Features Applications/Uses Key Specifications Diagram

# **Technical Documents**

Data Sheet Application Notes Design Guides Engineering Journals Reliability Reports Software/Models Evaluation Kits

# **Ordering Info**

Price and Availability Samples Buy Online Package Information Lead-Free Information

# More Information

Related Products Notes and Comments Evaluation Kits

Document Ref.: 19-4273; Rev 0; 2008-09-12 This page last modified: 2008-09-12

Contact Us • Rate This Page • Mail This Page • Privacy Policy • Legal Notices

Copyright © 2009 by Maxim Integrated Products