



Micro Commercial Components 20736 Marilla Street Chatsworth

CA 91311

Phone: (818) 701-4933 (818) 701-4939 Fax:

**HER301 Thru HER308** 

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Low forward voltage drop
- High reliability and High surge current capability
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1 Halogen free available upon request by adding suffix "-HF"

# **Maximum Ratings**

Operating Temperature:  $-55^{\circ}$ C to  $+150^{\circ}$ C Storage Temperature: -55°C to +150°C

Typical Thermal Resistance: 30°C/W Junction To Lead

MCC Part	Device	Maximum	Maximum	Maximum
Number	Marking	Recurrent	RMS	DC
		Peak Reverse	Voltage	Blocking
		Voltage		Voltage
HER301	HER301	50V	35V	50V
HER302	HER302	100V	70V	100V
HER303	HER303	200V	140V	200V
HER304	HER304	300V	210V	300V
HER305	HER305	400V	280V	400V
HER306	HER306	600V	420V	600V
HER307	HER307	800V	560V	800V
HER308	HER308	1000V	700V	1000V

## Electrical Characteristics @ $25^{\circ}$ Unless Otherwise Specified

Average Forward Current	I <sub>F(AV)</sub>	3.0A	T <sub>A</sub> = 55°C
Peak Forward Surge Current	I <sub>FSM</sub>	150A	8.3ms, half sine
Maximum Instantaneous Forward Voltage HER301-HER303 HER304-HER305 HER306-HER308	V <sub>F</sub>	1.0V 1.3V 1.7V	$I_{FM} = 3.0A;$ $T_A = 25^{\circ}C$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	10uA 200uA	T <sub>A</sub> = 25°C T <sub>A</sub> = 100°C
Maximum Reverse Recovery Time HER301-HER305 HER306-HER308	Trr	50ns 75ns	I <sub>F</sub> =0.5A, I <sub>R</sub> =1.0A I <sub>RR</sub> =0.25A
Typical Junction Capacitance HER301-HER305 HER306-HER308	С	80pF 50pF	Measured at 1.0MHz, V <sub>R</sub> =4.0V


Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

**DO-201AD** 

3.0 Amp High

**Efficient Rectifiers** 

50 to 1000 Volts



DIMENSIONS							
	INCHES		MM				
DIM	MIN	MAX	MIN	MAX	NOTE		
Α	.287	.374	7.30	9.50			
В	.189	.208	4.80	5.30			
С	.048	.052	1.20	1.30			
D	1.000		25.40				



# HER301 THRU HER308

### RATINGS AND CHARACTERISTIC CURVES

FIG.1- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




FIG.2- MAXIMUM AVERAGE FORWARD CURRENT DERATING




FIG.3- TYPICAL REVERSE CHARACTERISTICS







FIG.5- TYPICAL FORWARD CHARACTERISTICS



INSTANTANEOUS FORWARD VOLTAGE, VOLTS







## Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 1.2Kpcs/Reel
Part Number-AP	Ammo Packing: 1.2Kpcs/Ammo Box
Part Number-BP	Bulk: 12Kpcs/Carton

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.