



## ISOTOP® Boost chopper NPT IGBT

**$V_{CES} = 600V$**   
 **$I_C = 60A @ T_c = 95^\circ C$**



### Application

- AC and DC motor control
- Switched Mode Power Supplies
- Power Factor Correction
- Brake switch

### Features

- Non Punch Through (NPT) THUNDERBOLT IGBT
  - Low voltage drop
  - Low tail current
  - Switching frequency up to 100 kHz
  - Soft recovery parallel diodes
  - Low diode VF
  - Low leakage current
  - Avalanche energy rated
  - RBSOA and SCSOA rated
- ISOTOP® Package (SOT-227)
- Very low stray inductance
- High level of integration

### Benefits

- Outstanding performance at high frequency operation
- Stable temperature behavior
- Very rugged
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Easy paralleling due to positive  $T_C$  of  $V_{CEsat}$
- RoHS Compliant

### Absolute maximum ratings

| Symbol            | Parameter  |                |                       | Max ratings | Unit |
|-------------------|--|----------------|-----------------------|-------------|------|
| V <sub>CES</sub>  | Collector - Emitter Breakdown Voltage                    |                |                       | 600         | V    |
| I <sub>C1</sub>   | Continuous Collector Current                             |                | T <sub>C</sub> = 25°C | 93          | A    |
| I <sub>C2</sub>   |  |                | T <sub>C</sub> = 95°C | 60          |      |
| I <sub>CM</sub>   | Pulsed Collector Current                                 |                | T <sub>C</sub> = 25°C | 360         |      |
| V <sub>GE</sub>   | Gate – Emitter Voltage                                   |                |                       | ±20         | V    |
| P <sub>D</sub>    | Maximum Power Dissipation                                |                | T <sub>C</sub> = 25°C | 378         | W    |
| I <sub>LM</sub>   | RBSOA clamped Inductive load Current R <sub>G</sub> =11Ω |                | T <sub>C</sub> = 25°C | 360         | A    |
| I <sub>FAV</sub>  | Maximum Average Forward Current                          | Duty cycle=0.5 | T <sub>C</sub> = 80°C | 30          | A    |
| I <sub>FRMS</sub> | RMS Forward Current (Square wave, 50% duty)              |                |                       | 39          |      |

**CAUTION:** These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.

**All ratings @  $T_j = 25^\circ\text{C}$  unless otherwise specified**

**Electrical Characteristics**

| Symbol        | Characteristic                       | Test Conditions                                  | Min   | Typ | Max        | Unit          |
|---------------|--------------------------------------|--|---|-----|------------|---------------|
| $I_{CES}$     | Zero Gate Voltage Collector Current  | $V_{GE} = 0\text{V}$<br>$V_{CE} = 600\text{V}$   | $T_j = 25^\circ\text{C}$<br>$T_j = 125^\circ\text{C}$ |     | 80<br>2000 | $\mu\text{A}$ |
| $V_{CE(sat)}$ | Collector Emitter saturation Voltage | $V_{GE} = 15\text{V}$<br>$I_C = 60\text{A}$      | $T_j = 25^\circ\text{C}$<br>$T_j = 125^\circ\text{C}$ | 2.0 | 2.5<br>2.8 | V             |
| $V_{GE(th)}$  | Gate Threshold Voltage               | $V_{GE} = V_{CE3}$ , $I_C = 500\mu\text{A}$      |   | 3   | 4          | 5             |
| $I_{GES}$     | Gate – Emitter Leakage Current       | $V_{GE} = \pm 20\text{V}$ , $V_{CE} = 0\text{V}$ |   |     | $\pm 100$  | nA            |

**Dynamic Characteristics**

| Symbol       | Characteristic               | Test Conditions                             | Min | Typ  | Max  | Unit |
|--------------|------------------------------|---|-----|------|------|------|
| $C_{ies}$    | Input Capacitance            | $V_{GE} = 0\text{V}$                        |     | 3125 | 3590 | pF   |
| $C_{oes}$    | Output Capacitance           | $V_{CE} = 25\text{V}$                       |     | 310  | 450  |      |
| $C_{res}$    | Reverse Transfer Capacitance | $f = 1\text{MHz}$                           |     | 180  | 310  |      |
| $Q_g$        | Total gate Charge            | $V_{GS} = 15\text{V}$                       |     | 257  | 410  | nC   |
| $Q_{ge}$     | Gate – Emitter Charge        | $V_{Bus} = 300\text{V}$                     |     | 19   | 30   |      |
| $Q_{gc}$     | Gate – Collector Charge      | $I_C = 60\text{A}$                          |     | 120  | 180  |      |
| $T_{d(on)}$  | Turn-on Delay Time           | Resistive Switching ( $25^\circ\text{C}$ )  |     | 20   | 40   | ns   |
| $T_r$        | Rise Time                    | $V_{GE} = 15\text{V}$                       |     | 95   | 190  |      |
| $T_{d(off)}$ | Turn-off Delay Time          | $V_{Bus} = 300\text{V}$                     |     | 315  | 470  |      |
| $T_f$        | Fall Time                    | $I_C = 60\text{A}$<br>$R_G = 5\Omega$       |     | 245  | 490  |      |
| $T_{d(on)}$  | Turn-on Delay Time           | Inductive Switching ( $25^\circ\text{C}$ )  |     | 26   | 50   | ns   |
| $T_r$        | Rise Time                    | $V_{GE} = 15\text{V}$                       |     | 63   | 125  |      |
| $T_{d(off)}$ | Turn-off Delay Time          | $V_{Bus} = 400\text{V}$                     |     | 395  | 590  |      |
| $T_f$        | Fall Time                    | $I_C = 60\text{A}$<br>$R_G = 5\Omega$       |     | 68   | 140  |      |
| $E_{ts}$     | Total switching Losses       |   |     | 3.4  | 7    | mJ   |
| $T_{d(on)}$  | Turn-on Delay Time           | Inductive Switching ( $150^\circ\text{C}$ ) |     | 25   | 50   | ns   |
| $T_r$        | Rise Time                    | $V_{GE} = 15\text{V}$                       |     | 59   | 120  |      |
| $T_{d(off)}$ | Turn-off Delay Time          | $V_{Bus} = 400\text{V}$                     |     | 430  | 650  |      |
| $T_f$        | Fall Time                    | $I_C = 60\text{A}$<br>$R_G = 5\Omega$       |     | 65   | 130  |      |
| $E_{on}$     | Turn-on Switching Energy     |   |     | 1.6  | 3.2  | mJ   |
| $E_{off}$    | Turn-off Switching Energy    |   |     | 2.4  | 4.8  |      |
| $E_{ts}$     | Total switching Losses       |   |     | 4.0  | 8.0  |      |








**Chopper diode ratings and characteristics**

| Symbol           | Characteristic                   | Test Conditions   | Min                    | Typ  | Max | Unit |
|------------------|----------------------------------|---|------------------------|------|-----|------|
| V <sub>F</sub>   | Diode Forward Voltage            | I <sub>F</sub> = 30A  |                        | 1.6  | 1.8 | V    |
|                  |                                  | I <sub>F</sub> = 60A  |                        | 1.9  |     |      |
|                  |                                  | I <sub>F</sub> = 30A    T <sub>j</sub> = 125°C  |                        | 1.4  |     |      |
| I <sub>RM</sub>  | Maximum Reverse Leakage Current  | V <sub>R</sub> = 600V    T <sub>j</sub> = 25°C  |                        |      | 250 | μA   |
|                  |                                  | V <sub>R</sub> = 600V    T <sub>j</sub> = 125°C                                       |                        |      | 500 |      |
| C <sub>T</sub>   | Junction Capacitance             | V <sub>R</sub> = 200V   |                        | 44   |     | pF   |
| t <sub>rr</sub>  | Reverse Recovery Time            | I <sub>F</sub> = 1A, V <sub>R</sub> = 30V<br>di/dt = 100A/μs    T <sub>j</sub> = 25°C |                        | 23   |     | ns   |
|                  | Reverse Recovery Time            |   | T <sub>j</sub> = 25°C  | 85   |     |      |
|                  |                                  |   | T <sub>j</sub> = 125°C | 160  |     |      |
| I <sub>RRM</sub> | Maximum Reverse Recovery Current | I <sub>F</sub> = 30A<br>V <sub>R</sub> = 400V<br>di/dt = 200A/μs                      | T <sub>j</sub> = 25°C  | 4    |     | A    |
|                  |                                  |   | T <sub>j</sub> = 125°C | 8    |     |      |
| Q <sub>rr</sub>  | Reverse Recovery Charge          |   | T <sub>j</sub> = 25°C  | 130  |     | nC   |
|                  |                                  |   | T <sub>j</sub> = 125°C | 700  |     |      |
| t <sub>rr</sub>  | Reverse Recovery Time            | I <sub>F</sub> = 30A  | T <sub>j</sub> = 125°C | 70   |     | ns   |
| Q <sub>rr</sub>  | Reverse Recovery Charge          | V <sub>R</sub> = 400V   |                        | 1300 |     | nC   |
| I <sub>RRM</sub> | Maximum Reverse Recovery Current | di/dt = 1000A/μs  |                        | 30   |     | A    |

**Thermal and package characteristics**

| Symbol                            | Characteristic   |       | Min  | Typ  | Max  | Unit |
|-----------------------------------|--|-------|------|------|------|------|
| R <sub>thJC</sub>                 | Junction to Case Thermal Resistance  | IGBT  |      |      | 0.33 | °C/W |
|                                   |  | Diode |      |      | 1.21 |      |
| R <sub>thJA</sub>                 | Junction to Ambient (IGBT & Diode)   |       |      |      | 20   |      |
| V <sub>ISOL</sub>                 | RMS Isolation Voltage, any terminal to case t = 1 min, 50/60Hz               |       | 2500 |      |      | V    |
| T <sub>J</sub> , T <sub>STG</sub> | Storage Temperature Range  |       | -55  |      | 150  | °C   |
| T <sub>L</sub>                    | Max Lead Temp for Soldering: 0.063" from case for 10 sec                     |       |      |      | 300  |      |
| Torque                            | Mounting torque (Mounting = 8-32 or 4mm Machine and terminals = 4mm Machine) |       |      |      | 1.5  | N.m  |
| Wt                                | Package Weight   |       |      | 29.2 |      | g    |

## Typical IGBT Performance Curve






Figure 8, Typical  $V_{CE(SAT)}$  Voltage vs Junction Temperature




Figure 10, Breakdown Voltage vs Junction Temperature




Figure 12, Typical Switching Energy Losses vs. Junction Temperature




Figure 9, Maximum Collector Current vs Case Temperature




Figure 11, Typical Switching Energy Losses vs Gate Resistance




Figure 13, Typical Switching Energy Losses vs Collector Current




Figure 14, Typical Load Current vs Frequency




Figure 15, Switching Loss Test Circuit and Waveforms




Figure 16, Resistive Switching Time Test Circuit and Waveforms

## Typical Diode Performance Curve




FIGURE 1a. MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs. PULSE DURATION




FIGURE 1b, TRANSIENT THERMAL IMPEDANCE MODEL




Figure 2. Forward Current vs. Forward Voltage




Figure 4. Reverse Recovery Charge vs. Current Rate of Change




Figure 6. Dynamic Parameters vs. Junction Temperature




Figure 8. Junction Capacitance vs. Reverse Voltage




Figure 3. Reverse Recovery Time vs. Current Rate of Change




Figure 5. Reverse Recovery Current vs. Current Rate of Change




Figure 7. Maximum Average Forward Current vs. Case Temperature




Figure 9. Diode Test Circuit





Figure 10. Diode Reverse Recovery Waveform and Definitions

## SOT-227 (ISOTOP®) Package Outline



ISOTOP® is a registered trademark of ST Microelectronics NV



### DISCLAIMER

The information contained in the document (unless it is publicly available on the Web without access restrictions) is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be approved by Microsemi in writing signed by an officer of Microsemi.

Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Any performance specifications believed to be reliable but are not verified and customer or user must conduct and complete all performance and other testing of this product as well as any user or customers final application. User or customer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the customer's and user's responsibility to independently determine suitability of any Microsemi product and to test and verify the same. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the User. Microsemi specifically disclaims any liability of any kind including for consequential, incidental and punitive damages as well as lost profit. The product is subject to other terms and conditions which can be located on the web at <http://www.microsemi.com/legal/tnc.asp>

### Life Support Application

Seller's Products are not designed, intended, or authorized for use as components in systems intended for space, aviation, surgical implant into the body, in other applications intended to support or sustain life, or for any other application in which the failure of the Seller's Product could create a situation where personal injury, death or property damage or loss may occur (collectively "Life Support Applications").

Buyer agrees not to use Products in any Life Support Applications and to the extent it does it shall conduct extensive testing of the Product in such applications and further agrees to indemnify and hold Seller, and its officers, employees, subsidiaries, affiliates, agents, sales representatives and distributors harmless against all claims, costs, damages and expenses, and attorneys' fees and costs arising, directly or indirectly, out of any claims of personal injury, death, damage or otherwise associated with the use of the goods in Life Support Applications, even if such claim includes allegations that Seller was negligent regarding the design or manufacture of the goods.

Buyer must notify Seller in writing before using Seller's Products in Life Support Applications. Seller will study with Buyer alternative solutions to meet Buyer application specification based on Sellers sales conditions applicable for the new proposed specific part.