


Microsemi provides very high frequency RF ICs and packaged modulator drivers for high speed/high frequency 100G+ optical transceivers for long haul, metro and datacenter applications. We are developing a new generation of surface mount drivers that provide industry leading signal to noise ratio in a compact package with competitive power dissipation. Many of our products offer the unique capability to be used in limiting or linear mode by simply changing the bias conditions and drive levels. In addition, we offer features such as gain control and peak detection. Our products target a range of form factors such MSA, CFP/CFP2/CFP4 and QSFP28.


Limiting Output Voltage (Vpp)	Linear Output Voltage (Vpp)	Bit Rate (Gb/s)	Bandwidth (GHz)	Input/ Output Port Configuration	Number of Channels	Gain (dB)	Package	Part Number
8.0	na	32	27	SE/SE	4	26	Connectorized	OA3MHQM
8.0	na	32	27	SE/SE	4	26	Connectorized	OA3MHQM-2
7.5	5.0	>32	35	SE/SE	4	20	Connectorized	OA3MMQM
7.5	5.0	32	26	DIFF/SE	4	20 to 31	SMT	OA3HVQDSL
6.0	4.0	32	26	DIFF/SE	4	14 to 25	SMT	OA3HVQDSL2
5.5	4.5	32	26	DIFF/DIFF	4	15 to 26	SMT	OA3HMQDDL
3	2.5	32	26	SE/SE	4	15	SMT	OA3SSQL
2.5	2	112	34	DIFF/DIFF	1	10 to 23	SMT	Tiger

Typical 32 Gb/s 7.5Vpp NRZ output eye, OA3HVQDSL



Parameter	Value
Eye Amplitude	7.5 V
Eye Height	5.8 V
Eye S/N	13
Crossing %	48%

Typical 32 Gb/s 4Vpp PAM-4 output eye, OA3HVQDSL2




Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi describes not grant, explicitly to any party any patter rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information provided in this document or to any products and services at any time without notice.




Microsemi Optical Solutions


Products Selection Guide




MSA



CFP2-ACO



QSFP28









Microsemi Corporate Headquarters One Enterprise, Aliso Viejo, CA 92656 USA Within the USA: +1 (800) 713-4113 Outside the USA: +1 (949) 380-6100 Sales: +1 (949) 380-6136 Fax: +1 (949) 380-6136 email: sales.support@microsemi.com www.microsemi.com Microsemi Corporation (MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense & security, aerospace and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 4,800 employees globally. Learn more at www.microsemi.com

©2016 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.