





PCB LAYOUT

- Note: Not end stackable.
- Accepts JEDEC PLCCs MO-047 & MO-052.
- Insulator material is glass reinforced PPS.
- Low profile for high density PC board stacking.
- Standoffs provide clearance for heat dissipation and cleaning.
- Contacts are plated with 150μ" tin/lead.
- Pre-lubricated available. (See page 96 for specs.)



No. of contacts	A	B	C	Ordering Information
20	0.600	0.200	0.404	940-99-020-17-40X00X
28	0.700	0.300	0.504	940-99-028-17-40X00X
32*	.800/.700	.400/.300	.600/.504	940-99-032-17-40X00X
44	0.900	0.500	0.704	940-99-044-17-40X00X
52	1.000	0.600	0.804	940-99-052-17-40X00X
68	1.213	0.800	1.004	940-99-068-17-40X00X
84	1.413	1.000	1.204	940-99-084-17-40X00X

*RECTANGULAR

X = 0 Not Lubricated

X = 1 Pre-Lubricated

X = 0 Tube Packaging

X = 4 Tape and Reel

No. of Contacts	Quantity per Tube	Quantity per Reel
20	32	400
28	27	400
32	24	400
44	21	250
52	19	250
68	16	250
84	14	250