

# Datasheet for 76650-0046

| General Information    |  |  |  |
|------------------------|--|--|--|
| Part Number:           | 76650-0046   |  |  |
| Manufacturer:          | Molex / Waldom   |  |  |
| Title:<br>Description: | Solderless Terminal Kit<br>.187" Tab Size Nylon Insulated and Fully Insulated Quick Disconnect Solderless<br>Terminals |  |  |
| Product Family:        | Quick Disconnects  |  |  |
| Certificates:          | (Molex Parts within this kit) - EU RoHS Compliant, UL and CSA  |  |  |
| Country of Origin:     | Kit assembled in U.S.A.  |  |  |

## Specifications

| Design<br>Configuration: | Wire-to-Wire / Solderless Terminals   |
|--------------------------|---------------------------------------|
| Tab Size:                | .187"                                 |
| Connector Type:          | Male and Female                       |
| Insulation:              | Nylon                                 |
| Current Rating:          | (3-15) Amps - Dependant on Wire Gauge |
| Voltage:                 | 300 Volts                             |
| Wire size:               | (22-18) and (16-14) AWG               |

### **Product Highlights**

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade.

| Features and Benefits  | Applications   |
|--|--|
| <ul> <li>Color-coded insulator allows easy identification of terminal size and wire gauge.</li> <li>A wire stop stamped into the crimp barrel prevents insertion of over-stripped wires.</li> <li>Terminal's funnel entrance is designed for increased crimping rates by speeding wire delivery into the crimp section and eliminating wire strand fold back.</li> </ul> | <ul> <li>MRO (Maintenance Repair and Operations)</li> <li>Consumer applications</li> <li>Power applications</li> <li>Motor applications</li> </ul> |

For additional Molex / Waldom Design and Solution kits please go to www.molexkits.com



# Datasheet for 76650-0046

#### Bill of Materials for Part No. 76650-0046

| Molex Part No. | Country<br>of Origin | Description   | Quantity in Kit |
|----------------|----------------------|---|-----------------|
|                | l ci ci igini        |   |                 |
| 19002-0005     | USA                  | Fully Insulated .187" Female Quick Disconnects, 22-18 AWG | 5               |
| 19002-0028     | USA                  | Fully Insulated .187" Female Quick Disconnects, 16-14 AWG | 5               |
| 19019-0006     | USA                  | Insulated .187" Female Quick Disconnects, 22-18 AWG       | 20              |
| 19019-0027     | USA                  | Insulated .187" Female Quick Disconnects, 16-14 AWG       | 20              |
| 19025-0002     | USA                  | Insulated .187" Male Quick Disconnects, 22-18 AWG         | 25              |
| 19025-0008     | USA                  | Insulated .187" Male Quick Disconnects, 16-14 AWG         | 25              |

### Recommended Molex Tool(s) for Part No. 76650-0046\*

| of Origin | Description                            |
|-----------|--|
| USA       | Hand Crimp Tool (RHT-1990)             |
| USA       | Hand Crimp Tool (RHT-1991)             |
| USA       | Hand Crimp Tool (RHT-5760)             |
| USA       | Hand Crimp Tool (RHT-5762)             |
| USA       | Hand Crimp Tool (RHT-2100)             |
| USA       | Hand Crimp Tool (RHT-5757)             |
| USA       | Hand Crimp Tool (RHT-5758)             |
|           | USA<br>USA<br>USA<br>USA<br>USA<br>USA |

\*Tool(s) not included in kit. Tool(s) ordered separately.