

#### **General Information**

Kit Part Number: <u>76650-0125</u>

**Description:** Friction Lock Plug and Receptacle

Application: Automotive / Transportation, Consumer Products, Industrial Equipment, Medical

Connector Family: PicoBladeâ,,¢

**Solution:** Free Hanging Connectors

Connector Type: Wire-to-Wire

Number of Pieces: 300 RoHS: Yes

## **Specifications**

**Adapter Family:** 2, 3, 6, 10

Current Rating: 1A

Mounting Style: Free-Hanging

Orientation: Receptacles, Plugs

**Pitch:** 1.25mm (.049")

Tool Included: No
Voltage Rating: 125V
Wire Gauge (AWG): 32-28

#### **Product Highlights**

#### **Product Highlights**

1.25mm (.049") pitch PicoBlade™ system is designed for high-density harness applications. PicoBlade™ provides the same 1.0 amperes of current as similar 2.00mm (.079") pitch systems, but in a more compact design. PicoBlade™ is offered in wire-to-board and wire-to-wire options. The system saves about 45% of PCB space compared to typical 2.00mm wire-to-board systems. It is a single row system, available in 2 to 15 circuits, with both surface mount and through-hole headers.

### Features and Benefits

- Reliable terminal for solid electrical connection
- Friction lock for good mating retention
- Polarizing features ensures proper mating orientation
- Two solder tabs for better connection to the PCB

## Applications

- Car Radios
- Process controls
- Cash dispensers
- Patient monitors
- Alarm systems
- Set top boxes
- DVD players



## **Bill of Materials**

Part No.	Qty In Kit	Description	Datasheet	P/N Details	
51047-0200	10	1.25mm (.049") Pitch PicoBlade™ Plug , 2 Circuits	<u>Datasheet</u>	<u>Details</u>	
<u>51021-0600</u>	10	1.25mm (.049") Pitch PicoBlade™ Receptacle, 6 Circuits	<u>Datasheet</u>	<u>Details</u>	
<u>51047-0300</u>	20	1.25mm (.049") Pitch PicoBlade™ Plug, 3 Circuits	<u>Datasheet</u>	<u>Details</u>	
<u>51047-0600</u>	10	1.25mm (.049") Pitch PicoBlade™ Plug, 6 Circuits	<u>Datasheet</u>	<u>Details</u>	
<u>51047-1000</u>	10	1.25mm (.049") Pitch PicoBlade™ Plug, 10 Circuits	<u>Datasheet</u>	<u>Details</u>	
51021-0200	10	1.25mm (.049") Pitch PicoBlade™ Receptacle, 2 Circuits	<u>Datasheet</u>	<u>Details</u>	
51021-0300	20	1.25mm (.049") Pitch PicoBlade™ Receptacle, 3 Circuits	<u>Datasheet</u>	<u>Details</u>	
51021-1000	10	1.25mm (.049") Pitch PicoBlade™ Receptacle, 10 Circuit	<u>Datasheet</u>	<u>Details</u>	
50058-8000	100	PicoBlade™ Crimp Terminal, Female, 32-28 AWG	<u>Datasheet</u>	<u>Details</u>	
50133-8100	100	PicoBlade™ Crimp Terminal, Male, 32-28 AWG	<u>Datasheet</u>	<u>Details</u>	

# **Recommended Tool**

Part No.	Included in Kit
63819-0400	No
<u>11-03-0043</u>	No
<u>63819-0300</u>	No
<u>63900-3700</u>	No
<u>63811-0000</u>	No
<u>63910-3700</u>	No
<u>63820-7000</u>	No
<u>63860-7000</u>	No
<u>57067-3200</u>	No
<u>57072-6000</u>	No
<u>57139-5000</u>	No











