1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



Datasheet for 76650-0153

General Information

Part Number: 76650-0153

Manufacturer: Molex / Waldom

Title: Solderless Terminal Kit

Nylon Insulated .250" Tab Size Quick Disconnect, Quick Disconnect Adaptor and

Description: Coupler

Product Family: Quick Disconnects

Certificates: (Molex Parts within this kit) - EU RoHS Compliant

Country of Origin: Kit assembled in U.S.A.

Specifications

Design

Configuration: Wire-to-Wire / Solderless Terminals

Tab Size: .250"

Connector Type: Male and Female

Insulation: Nylon

Current Rating: (3-15) Amps - Dependant on Wire Gauge

Voltage: 300 Volts

Wire size: (22-18), (16-14), (14-12) and (12-10) AWG

Product Highlights

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade. Quick Disconnects (QDs) are female terminals that mate with male tab terminals, tab adapters, and terminal blocks fitted with male tabs.

Features and Benefits

Applications



Datasheet for 76650-0153

- Color-coded insulator allows easy indentification of terminal size and wire gauge.
- Avikrimp provides a metal insulation support sleeve for superior strain relief
- These fulfill the double crimp (support) requirements of VDE and other DIN specifications
- Make two .250" x .032" male tabs from one male tab when an add-on circuit is needed
- Converts one Power Block 1/4" (female) to two male tabs 10 deg. bend-up; 120 deg. bend-back
- Splices two female 1/4" quick connects

- MRO (Maintenance Repair and Operations)
- Consumer applications
- Power applications
- Motor applications

Bill of Materials for Part No. 76650-0153

Country Molex Part No. of Origin Description **Quantity in Kit USA** 19019-0012 .250 x .032 Nylon Female Quick Disconnects (22-18) AWG 25 USA 19019-0031 .250 x .032 Nylon Female Quick Disconnects (16-14) AWG 25 19019-0052 **USA** .250 x .032 Nylon Female Quick Disconnects (14-12) AWG 25 19019-0037 USA 25 .250 x .032 Nylon Female Quick Disconnects (12-10) AWG .250 x .032 Double Male / Single Female Quick Disconnect 19043-0001 USA Adapter 10 19043-0010 Taiwan .250 x .032 Three Way Quick Disconnect Adapter 10 Taiwan .250 x .032 Double Male Quick Disconnect Insulated Coupler 5 19163-0178

Recommended Molex Tool(s) for Part No. 76650-0153*

	Country	
Molex Part No.	of Origin	Description
64001-0200 *	USA	Hand Crimp Tool (RHT-1991) / (22-18) AWG
64001-1700 *	USA	Hand Crimp Tool (RHT-5757) / (22-18) AWG
64001-1800 *	USA	Hand Crimp Tool (RHT-5759) / (14-12) AWG
64001-2000 *	USA	Hand Crimp Tool (RHT-5758) / (16-14) AWG
64001-7300 *	USA	Hand Crimp Tool (RHT-2210) / (12-10) AWG

^{*}Tool(s) not included in kit. Tool(s) ordered separately.