LFH Page 1 of 2

> Register // Login My Parts (0 items) **Contact Molex**

Connectors Assemblies Home Shielded Input/Output (I/O) LFH™ Tooling

Sockets

Search: Enter Part No. or Keyword

Cable

1/0

Printed Circuit Industrial Products Products

Lighting Products

Refine Search

Connectors

Product Family (Please choose this first) Product Name Product Series Circuits (Loaded) Circuits (maximum)

Pitch - Mating Interface

Current - Maximum per Contact Orientation

Wire Size AWG

Low-Halogen Status

LFH™ - Application Tooling

Go

Fiber Optics

Manual Press for Stick Preparation
Semi-Automatic Weld Termination Unit
Stick Loading Tool
Ferrule Crimp - Hand Tool Ferrule Crimp - Manual Press

Manual Press for Stick Preparation

Features

- Removes carrier strip and trims terminal tail to correct length for welding
 Removes busbar either selectively or completely to accommodate all possible bussing options
 Die set construction installs easily into standard manual press

Specifications

- Size: Width-230mm (9") Depth-350mm (14") Height-530mm (21")
 Weight: 29.5kg (65 lb)
 Rate: Up to 150 LFH sticks per hour, dependent on operator speed

Ordering Information for Manual Press for Stick Preparation

Order No. 11-31-6356 Basic Press
Order No. 62200-1100 LFH Stick Preparation Tool Kit
Use with LFH Terminal Stick: 51-24-2201, 51-25-2011, 70984-4000, 70984-1007,
70984-1010, 70984-4003, 70984-4008

Return to List of LFH Application Tools

Semi-Automatic Weld Termination Unit

- Wire is fixtured in clamps mounted on removable pallet, which may be prepared
- off line to increase productivity

 Up to 25 jobs can be stored in machine memory

 Job storage data includes stick circuit size and pitch, void positions and welding parameters specific to the job

 Operator can inspect with position (via zoom video microscope) prior to welding
- - Weld power supply has built-in process monitor Touch screen operator control panel
 - Unit is integrated into free-standing workstation

Specifications

- Size: Width--1500mm (60") Depth--800mm (32") Height--1900mm (76")
 Weight: 140kg (300 lb)
 Pneumatics: Pressure--5.4 BAR (80psig) Consumption--14L per minute (0.5 CFM)
- Electrical: Voltage-120V, 50 to 60 Hz Current-10.0A

 Rate: Up to 14 fully terminated 60 circuit (7 fully terminated 160 circuit) LFH connectors per hour, dependent on operator speed and application

Ordering Information for Semi-Automatic Weld Termination Unit

Order No. 11-20-1330 Semi-Automatic Weld Terminator with 1 pallet and 1 set of standard (28 AWG, .035" OD) wire clamps
Order No. 11-20-1344 Additional pallet with 1 set of stand wire clamps Use with LFH Terminal Stick: 51-24-2021, 51-25-2011, 70984-4008, 70984-1007, 70984-1007, 70984-1010, 70984-4003, 70984-4008

Return to List of LFH Application Tools

Stick Loading Tool

Features

- Used for inserting terminated LFH sticks into LFH connector housing
 - All 4 sticks are simultaneously inserted
 Stick-holding nest has feature to prevent loading sticks upside down
- Insertion lever has positive stop for consistent insertions
 - Holes provided for mounting to workbench

Specifications

LFH Page 2 of 2

- Size:Width--400mm (16") Depth--250mm (10") Height--130mm (5")
 Weight: 11.3kg (25 lb)
- Rate: Up to 60 plugs per hour, dependent on operator speed and application

Ordering Information for Stick Loading Tool

Description Stick Insertion Tool	Order No. Complete Tool	Tool Kit Only	Use with Connector
60 Circuit Plug	62200-1500	62200-0800	70929-2000
60 Circuit Receptacle	62200-1600	62200-0900	71691-0003
160 Circuit Plug	62200-1700	62200-1000	71624-3000

Return to List of LFH Application Tools **Ferrule Crimp - Hand Tool**

Features

- Crimp die has 2 positions to crimp the large and small diameter in a 2 step operation
 - For low volume, prototype or repairs

Ordering Information for Ferrule Crimp Hand Tool

Description	Order No.	For Ferrule No.
Ferrule Hand Tool with Dies	62100-0100	71256-0001
Ferrule Hand Tool with Dies	62100-0200	71256-0002
Untooled Hand Tool	11-31-6379	
Ferrule Crimping Die	62100-0101	71256-0001
Ferrule Crimping Die	62100-0201	71256-0002

Return to List of LFH Application Tools **Ferrule Crimp - Manual Press**

Features

- Able to crimp both large and small diameter of the ferrule in 1 step
- Ratchet terminator assures completion of full cycle

 Modularity, able to use same press for stick prep and ferrule crimp with a simple die change

Ordering Information for Ferrule Crimp Manual Press

Description	Order No.	For Ferrule No.
Manual Press with Dies & Fixture	62200-1200	71256-0001
Manual Press with Dies & Fixture	62200-1300	71256-0002
Untooled Manual Press with Fixture	11-21-9507	
Fixture Only	11-31-7559	
Ferrule Crimping Die	62200-1201	71256-0001
Ferrule Crimping Die	62200-1301	71256-0002

Return to List of LFH Application Tools

Other Info

Legal Disclaimer

Privacy Policy

Feedback

Sitemap

Help

Molex Connectors Wire-to-Board Board-to-Board Wire-to-Wire Input/Output (IO) FFC/FPC Sockets Fiber Optic

Other Products Industrial Automation Membrane Switches Copper Flex PCB Assemblies Woodhead Electrical Solid State Lighting

Resources Catalog Cross-Reference Industries Literature Product Name

Company Info About Us Careers Contact Us ecocare Investors Press Room

Stay Connected with Molex:







Copyright 2011