



Do-It-Yourself Option Available

FEATURES



- 7V to 36V Wide Operating Input
- 2.5A Load Current
- 5V Output Voltage
- Open Design Files and BOM
- Over-Current Protection
- Over-Temperature Protection
- Line Drop Compensation
- DCP for BC1.2, Divider Mode, and 1.2V/1.2V Mode

ORDERING INFORMATION

Part Number	Input Voltage (V)	Output Voltage (V)	Output Current (A)	Efficiency
MEZS91202A	7 - 36	5	2.5	Up to 95%


ELECTRICAL CHARACTERISTICS

Input Voltage Range	V_{IN} Continuous	7V to 36V
Output Voltage Set Accuracy		$\pm 4\%$ (Typ.)
Output Voltage Ripple	$V_{IN} = 12V$, Full Load	13mV
Line Regulation	$V_{IN} = 24V$	$\pm 0.5\%$ (Typ.)
Line Drop Compensation	Full Load	93%
Efficiency	$V_{IN} = 12V$, Full Load	93%
Switching Frequency	Typical Switching Frequency	350kHz
Short-Circuit Protection	Short Output to Ground	Hiccup Mode
Operating Temperature Range		-40 to 85°C
Over-Temperature Protection	OTP	165°C
Rise Time	From 10% V_{OUT} to 90% V_{OUT}	1.6ms (Typ.)
Calculated MTBF	MIL-HDBK-217F	4185x10 ³ hrs



NOTE: All electrical characteristics are tested under 25°C ambient temperature, $V_{IN} = 12V$ unless otherwise noted.


DO-IT-YOURSELF SCHEMATIC



BILL OF MATERIALS

Item	Qty	RefDes	Value	Description	Package	Manufacturer	Manufacturer P/N
1	5	C1, C1A, C1B, C1C, C1D	10μF	Ceramic Cap., 35V, X5R	0805	Murata	GRM21BR6YA106KE43L
2	1	C2	100μF	POSCAP, 6.3V, 15mΩ ESR	SMD, 7.3x4.3mm	Murata	ECASD40J107M015K00
3	1	C2A	1μF	Ceramic Cap., 10V, X5R	0402	Wurth	885012105012
4	1	C3	0.22μF	Ceramic Cap., 16V, X5R	0402	Wurth	885012105017
5	1	C4	0.1μF	Ceramic Cap., 10V, X7R	0402	Wurth	885012205018
6	1	C5	10μF	Ceramic Cap., 6.3V, X5R	0603	Wurth	885012106006
7	1	R1	300kΩ	Item	0603	Yageo	RC0603FR-07300KL
8	1	R2	1kΩ	Film Resistor, 1%	0402	Yageo	RC0402FR-071KL
9	1	LED	LED	LED, Green	0805	Kingbright	APHBM2012CGKSYKC
10	1	L1	6.5μH	Inductor, DCR = 21.5mΩ, Isat = 6A	SMD, 7.0x6.9mm	Wurth	744 314 650
11	1	USB	USB	Single USB Port	Tray	Wurth	61400416021
12	1	Connector	4-Pin	2.54mm Pitch		Wurth	613 004 110 21
13	1	U1	MP2496M	Step-Down Converter	QFN-26 (4mmx4mm)	MPS	MP2496MGR

PRODUCT PACKAGE AND DIMENSIONS



Pin	Designation	Function
1	VIN	Input Voltage
2	VIN	Input Voltage
3	GND	Power Ground
4	GND	Power Ground

NOTE:

Contact factory for different sizes of the boards (Quantity >2k).

For more information, Gerber files, and PCB layout, please contact mEZsupport@monolithicpower.com