

# 74F378

## Parallel D-Type Register with Enable

### General Description

The 74F378 is a 6-bit register with a buffered common Enable. This device is similar to the 74F174, but with common Enable rather than common Master Reset.

### Features


- 6-bit high-speed parallel register
- Positive edge-triggered D-type inputs
- Fully buffered common clock and enable inputs
- Input clamp diodes limit high-speed termination effects
- Full TTL and CMOS compatible

### Ordering Code:


| Order Number | Package Number | Package Description   |
|--------------|----------------|---|
| 74F378SC     | M16A           | 16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow |
| 74F378SJ     | M16D           | 16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| 74F378PC     | N16E           | 16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide       |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

### Logic Symbols



### Connection Diagram



74F378 Parallel D-Type Register with Enable

## Unit Loading/Fan Out

| Pin Names     | Description                            | U.L.<br>HIGH/LOW | Input $I_{IH}/I_{IL}$<br>Output $I_{OH}/I_{OL}$ |
|---------------|--|------------------|---|
| $\bar{E}$     | Enable Input (Active LOW)              | 1.0/1.0          | 20 $\mu$ A/-0.6 mA                              |
| $D_0$ - $D_5$ | Data Inputs                            | 1.0/1.0          | 20 $\mu$ A/-0.6 mA                              |
| CP            | Clock Pulse Input (Active Rising Edge) | 1.0/1.0          | 20 $\mu$ A/-0.6 mA                              |
| $Q_0$ - $Q_5$ | Outputs                                | 50/33.3          | -1 mA/20 mA                                     |

## Functional Description

The 74F378 consists of six edge-triggered D-type flip-flops with individual D inputs and Q outputs. The Clock (CP) and Enable ( $\bar{E}$ ) inputs are common to all flip-flops.


When the  $\bar{E}$  input is LOW, new data is entered into the register on the LOW-to-HIGH transition of the CP input. When the  $\bar{E}$  input is HIGH the register will retain the present data independent of the CP input.

## Truth Table

| Inputs    |    |       | Output    |
|-----------|----|-------|-----------|
| $\bar{E}$ | CP | $D_n$ | $Q_n$     |
| H         | ↗  | X     | No Change |
| L         | ↗  | H     | H         |
| L         | ↗  | L     | L         |

H = HIGH Voltage Level  
L = LOW Voltage Level  
X = Immaterial  
↗ = LOW-to-HIGH Clock Transition

## Logic Diagram



Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

**Absolute Maximum Ratings**(Note 1)

|  |                                      |
|--|--------------------------------------|
| Storage Temperature  | -65°C to +150°C                      |
| Ambient Temperature under Bias   | -55°C to +125°C                      |
| Junction Temperature under Bias  | -55°C to +150°C                      |
| V <sub>CC</sub> Pin Potential to Ground Pin                            | -0.5V to +7.0V                       |
| Input Voltage (Note 2)   | -0.5V to +7.0V                       |
| Input Current (Note 2)   | -30 mA to +5.0 mA                    |
| Voltage Applied to Output<br>in HIGH State (with V <sub>CC</sub> = 0V) |                                      |
| Standard Output  | -0.5V to V <sub>CC</sub>             |
| 3-STATE Output   | -0.5V to +5.5V                       |
| Current Applied to Output<br>in LOW State (Max)                        | twice the rated I <sub>OL</sub> (mA) |

**Recommended Operating Conditions**

|                              |                |
|------------------------------|----------------|
| Free Air Ambient Temperature | 0°C to +70°C   |
| Supply Voltage               | +4.5V to +5.5V |

**Note 1:** Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

**Note 2:** Either voltage limit or current limit is sufficient to protect inputs.

**DC Electrical Characteristics**

| Symbol           | Parameter                         | Min                                       | Typ        | Max  | Units | V <sub>CC</sub> | Conditions  |
|------------------|-----------------------------------|---|------------|------|-------|-----------------|---|
| V <sub>IH</sub>  | Input HIGH Voltage                | 2.0                                       |            |      | V     |                 | Recognized as a HIGH Signal                         |
| V <sub>IL</sub>  | Input LOW Voltage                 |   |            | 0.8  | V     |                 | Recognized as a LOW Signal                          |
| V <sub>CD</sub>  | Input Clamp Diode Voltage         |   |            | -1.2 | V     | Min             | I <sub>IN</sub> = -18 mA                            |
| V <sub>OH</sub>  | Output HIGH Voltage               | 10% V <sub>CC</sub><br>5% V <sub>CC</sub> | 2.5<br>2.7 |      | V     | Min             | I <sub>OH</sub> = -1 mA<br>I <sub>OH</sub> = -1 mA  |
| V <sub>OL</sub>  | Output LOW Voltage                | 10% V <sub>CC</sub>                       |            | 0.5  | V     | Min             | I <sub>OL</sub> = 20 mA                             |
| I <sub>IH</sub>  | Input HIGH Current                |   |            | 5.0  | μA    | Max             | V <sub>IN</sub> = 2.7V                              |
| I <sub>BVI</sub> | Input HIGH Current Breakdown Test |   |            | 7.0  | μA    | Max             | V <sub>IN</sub> = 7.0V                              |
| I <sub>CEX</sub> | Output HIGH Leakage Current       |   |            | 50   | μA    | Max             | V <sub>OUT</sub> = V <sub>CC</sub>                  |
| V <sub>ID</sub>  | Input Leakage Test                | 4.75                                      |            |      | V     | 0.0             | I <sub>ID</sub> = 1.9 μA<br>All Other Pins Grounded |
| I <sub>OD</sub>  | Output Leakage Circuit Current    |   |            | 3.75 | μA    | 0.0             | V <sub>ID</sub> = 150 mV<br>All Other Pins Grounded |
| I <sub>IL</sub>  | Input LOW Current                 |   |            | -0.6 | mA    | Max             | V <sub>IN</sub> = 0.5V                              |
| I <sub>OS</sub>  | Output Short-Circuit Current      | -60                                       |            | -150 | mA    | Max             | V <sub>OUT</sub> = 0V                               |
| I <sub>CCL</sub> | Power Supply Current              |   | 30         | 45   | mA    | Max             | V <sub>O</sub> = LOW                                |

### AC Electrical Characteristics

| Symbol           | Parameter               | T <sub>A</sub> = +25°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |     |     | T <sub>A</sub> = -55°C to +125°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |      | T <sub>A</sub> = 0°C to +70°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |     | Units |
|------------------|-------------------------|---|-----|-----|---|------|--|-----|-------|
|                  |                         | Min   | Typ | Max | Min   | Max  | Min  | Max |       |
| f <sub>MAX</sub> | Maximum Input Frequency | 80  | 100 |     | 70  |      | 80   |     | MHz   |
| t <sub>PLH</sub> | Propagation Delay       | 3.0   | 5.5 | 7.5 | 3.0   | 10.0 | 3.0  | 8.5 | ns    |
| t <sub>PHL</sub> | CP to Q <sub>n</sub>    | 3.5   | 6.0 | 8.5 | 3.5   | 10.5 | 3.5  | 9.5 |       |

### AC Operating Requirements



| Symbol             | Parameter               | T <sub>A</sub> = +25°C<br>V <sub>CC</sub> = +5.0V |     | T <sub>A</sub> = -55°C to +125°C<br>V <sub>CC</sub> = +5.0V |     | T <sub>A</sub> = 0°C to +70°C<br>V <sub>CC</sub> = +5.0V |     | Units |
|--------------------|-------------------------|---|-----|---|-----|--|-----|-------|
|                    |                         | Min   | Max | Min   | Max | Min  | Max |       |
| t <sub>S</sub> (H) | Setup Time, HIGH or LOW | 4.0   |     | 5.0   |     | 4.0  |     | ns    |
| t <sub>S</sub> (L) | D <sub>n</sub> to CP    | 4.0   |     | 5.0   |     | 4.0  |     |       |
| t <sub>H</sub> (H) | Hold Time, HIGH or LOW  | 0   |     | 2.0   |     | 0  |     |       |
| t <sub>H</sub> (L) | D <sub>n</sub> to CP    | 0   |     | 2.0   |     | 0  |     | ns    |
| t <sub>S</sub> (H) | Setup Time, HIGH or LOW | 6.0   |     | 4.5   |     | 6.0  |     |       |
| t <sub>S</sub> (L) | $\bar{E}$ to CP         | 10.0  |     | 13.0  |     | 10.0   |     |       |
| t <sub>H</sub> (H) | Hold Time, HIGH or LOW  | 0   |     | 0   |     | 0  |     | ns    |
| t <sub>H</sub> (L) | $\bar{E}$ to CP         | 0   |     | 0   |     | 0  |     |       |
| t <sub>W</sub> (H) | CP Pulse Width          | 4.0   |     | 5.0   |     | 4.0  |     | ns    |
| t <sub>W</sub> (L) | HIGH or LOW             | 6.0   |     | 7.5   |     | 6.0  |     |       |

**Physical Dimensions** inches (millimeters) unless otherwise noted



**16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow Package Number M16A**


**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)



DIMENSIONS ARE IN MILLIMETERS

- NOTES:  
 A. CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.  
 B. DIMENSIONS ARE IN MILLIMETERS.  
 C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.

M16DRevB1



**16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide Package Number M16D**

**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)



**16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide Package Number N16E**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)