

FDC6020C

Complementary PowerTrench® MOSFET

General Description

These N & P-Channel MOSFETs are produced using Fairchild Semiconductor's advanced PowerTrench process that has been especially tailored to minimize on-state resistance and yet maintain superior switching performance.



These devices are well suited for low voltage and battery powered applications where low in-line power loss and fast switching are required.

Applications

- DC/DC converter
- Load switch
- Motor Driving

Features

- **Q1** -4.2 A, -20V. $R_{DS(ON)} = 55\text{ m}\Omega @ V_{GS} = -4.5\text{ V}$
 $R_{DS(ON)} = 82\text{ m}\Omega @ V_{GS} = -2.5\text{ V}$
- **Q2** 5.9 A, 20V. $R_{DS(ON)} = 27\text{ m}\Omega @ V_{GS} = 4.5\text{ V}$
 $R_{DS(ON)} = 39\text{ m}\Omega @ V_{GS} = 2.5\text{ V}$
- Low gate charge
- High performance trench technology for extremely low $R_{DS(ON)}$.
- FLMP SSOT-6 package: Enhanced thermal performance in industry-standard package size



Absolute Maximum Ratings T_A = 25°C unless otherwise noted

Symbol	Parameter	Q1	Q2	Units
V _{DSS}	Drain-Source Voltage	-20	20	V
V _{GSS}	Gate-Source Voltage	±12	±12	V
I _D	Drain Current - Continuous (Note 1a)	-4.2	5.9	A
	- Pulsed	-20	20	
P _D	Power Dissipation for Dual Operation (Note 1a)	1.6		W
	Power Dissipation for single Operation (Note 1a)	1.8		
	(Note 1b)	1.2		
T _J , T _{STG}	Operating and Storage Junction Temperature Range	-55 to +150		°C

Thermal Characteristics

R _{θJA}	Thermal Resistance, Junction-to-Ambient (Note 1a)	68	°C/W
R _{θJC}	Thermal Resistance, Junction-to-Case (Note 1a)	1	

Package Marking and Ordering Information

Device Marking	Device	Reel Size	Tape width	Quantity
.020	FDC6020C	7"	8mm	3000 units

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
Off Characteristics							
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}$, $V_{GS} = 0\text{ V}$, $I_D = -250\ \mu\text{A}$ $I_D = 250\ \mu\text{A}$	Q1 Q2	-20 20			V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	$I_D = -250\ \mu\text{A}$, Referenced to 25°C $I_D = 250\ \mu\text{A}$, Referenced to 25°C	Q1 Q2		-14 12		mV/ $^\circ\text{C}$
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = -16\text{ V}$, $V_{DS} = 16\text{ V}$, $V_{GS} = 0\text{ V}$ $V_{GS} = 0\text{ V}$	Q1 Q2			-1 1	μA
I_{GSS}	Gate-Body Leakage	$V_{GS} = \pm 12\text{ V}$, $V_{GS} = \pm 12\text{ V}$, $V_{DS} = 0\text{ V}$ $V_{DS} = 0\text{ V}$	Q1 Q2			± 100 ± 100	nA
On Characteristics (Note 2)							
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$, $V_{DS} = V_{GS}$, $I_D = -250\ \mu\text{A}$ $I_D = 250\ \mu\text{A}$	Q1 Q2	-0.6 0.6	-1.0 1.0	-1.5 1.5	V
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate Threshold Voltage Temperature Coefficient	$I_D = -250\ \mu\text{A}$, Referenced to 25°C $I_D = 250\ \mu\text{A}$, Referenced to 25°C	Q1 Q2		3 -3		mV/ $^\circ\text{C}$
$R_{DS(on)}$	Static Drain-Source On-Resistance	$V_{GS} = -4.5\text{ V}$, $V_{GS} = -2.5\text{ V}$, $V_{GS} = -4.5\text{ V}$, $V_{GS} = 4.5\text{ V}$, $V_{GS} = 2.5\text{ V}$, $V_{GS} = 4.5\text{ V}$, $I_D = -4.2\text{ A}$, $I_D = -3.4\text{ A}$, $I_D = -4.2\text{ A}$, $I_D = 5.9\text{ A}$, $I_D = 4.9\text{ A}$, $I_D = 5.9\text{ A}$, $T_J = 125^\circ\text{C}$	Q1 Q2		45 65 58 23 33 31	55 82 73 27 39 39	m Ω
g_{FS}	Forward Transconductance	$V_{DS} = -5\text{ V}$, $V_{DS} = 5\text{ V}$, $I_D = -4.2\text{ A}$ $I_D = 5.9\text{ A}$	Q1 Q2		13 23		S
Dynamic Characteristics							
C_{iss}	Input Capacitance	Q1: $V_{DS} = -10\text{ V}$, $V_{GS} = 0\text{ V}$, $f = 1.0\text{ MHz}$	Q1 Q2		753 677		pF
C_{oss}	Output Capacitance	Q2: $V_{DS} = 10\text{ V}$, $V_{GS} = 0\text{ V}$, $f = 1.0\text{ MHz}$	Q1 Q2		163 171		pF
C_{rss}	Reverse Transfer Capacitance	$V_{DS} = 10\text{ V}$, $V_{GS} = 0\text{ V}$, $f = 1.0\text{ MHz}$	Q1 Q2		83 91		pF
R_G	Gate Resistance	$V_{GS} = 15\text{ mV}$, $f = 1.0\text{ MHz}$	Q1 Q2		8 2.2		Ω
Switching Characteristics							
$t_{d(on)}$	Turn-On Delay Time	Q1: $V_{DD} = -10\text{ V}$, $V_{GS} = -4.5\text{ V}$, $I_D = -1\text{ A}$, $R_{GEN} = 6\ \Omega$	Q1 Q2		13 11	23 20	ns
t_r	Turn-On Rise Time	Q2: $V_{DD} = 10\text{ V}$, $V_{GS} = 4.5\text{ V}$, $I_D = 1\text{ A}$, $R_{GEN} = 6\ \Omega$	Q1 Q2		8 16	16 29	ns
$t_{d(off)}$	Turn-Off Delay Time	Q1: $V_{DD} = 10\text{ V}$, $V_{GS} = 4.5\text{ V}$, $I_D = 1\text{ A}$, $R_{GEN} = 6\ \Omega$	Q1 Q2		26 18	42 32	ns
t_f	Turn-Off Fall Time	Q2: $V_{DD} = 10\text{ V}$, $V_{GS} = 4.5\text{ V}$, $I_D = 1\text{ A}$, $R_{GEN} = 6\ \Omega$	Q1 Q2		14 7	52 14	ns
Q_g	Total Gate Charge	Q1: $V_{DS} = -10\text{ V}$, $I_D = -4.2\text{ A}$, $V_{GS} = -4.5\text{ V}$	Q1 Q2		7 6	10 8	nC
Q_{gs}	Gate-Source Charge	Q2: $V_{DS} = 10\text{ V}$, $I_D = 5.9\text{ A}$, $V_{GS} = 4.5\text{ V}$	Q1 Q2		1.6 1.5		nC
Q_{gd}	Gate-Drain Charge	$V_{DS} = 10\text{ V}$, $I_D = 5.9\text{ A}$, $V_{GS} = 4.5\text{ V}$	Q1 Q2		1.9 1.8		nC

Electrical Characteristics (continued) $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
I_S	Maximum Continuous Drain-Source Diode Forward Current		Q1 Q2			-1.3 1.3	A
V_{SD}	Drain-Source Diode Forward Voltage	$V_{GS} = 0\text{ V}, I_S = -1.3\text{ A}$ (Note 2) $V_{GS} = 0\text{ V}, I_S = 1.3\text{ A}$ (Note 2)	Q1 Q2		-0.8 0.7	-1.2 1.2	V
t_{rr}	Diode Reverse Recovery Time	$I_F = -4.2\text{ A}, d_I/d_t = 100\text{ A}/\mu\text{s}$ $I_F = 5.9\text{ A}, d_I/d_t = 100\text{ A}/\mu\text{s}$	Q1 Q2		17 15		nS
Q_{rr}	Diode Reverse Recovery Charge	$I_F = -4.2\text{ A}, d_I/d_t = 100\text{ A}/\mu\text{s}$ $I_F = 5.9\text{ A}, d_I/d_t = 100\text{ A}/\mu\text{s}$	Q1 Q2		6 4		nC

Notes:

- $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.



- a) $68^\circ\text{C}/\text{W}$ when mounted on a 1 in^2 pad of 2 oz copper (Single Operation).



- b) $102^\circ\text{C}/\text{W}$ when mounted on a minimum pad of 2 oz copper (Single Operation).

Scale 1 : 1 on letter size paper

- Pulse Test: Pulse Width < $300\mu\text{s}$, Duty Cycle < 2.0%

Typical Characteristics : Q1




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

Typical Characteristics : Q1




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.




Figure 10. Single Pulse Maximum Power Dissipation.

Typical Characteristics : Q2




Figure 11. On-Region Characteristics.




Figure 12. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 13. On-Resistance Variation with Temperature.




Figure 14. On-Resistance Variation with Gate-to-Source Voltage.




Figure 15. Transfer Characteristics.




Figure 16. Body Diode Forward Voltage Variation with Source Current and Temperature.

Typical Characteristics : Q2




Figure 17. Gate Charge Characteristics.




Figure 18. Capacitance Characteristics.




Figure 19. Maximum Safe Operating Area.




Figure 20. Single Pulse Maximum Power Dissipation.






Figure 21. Transient Thermal Response Curve.

Thermal characterization performed using the conditions described in Note 1b. Transient thermal response will change depending on the circuit board design.


Dimensional Outline and Pad Layout



Bottom View



Top View



**Recommended Landing Pattern
For Standard Dual Configuration**

NOTES: UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE IN MILLIMETERS.

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FACT Quiet Series™	LittleFET™	Power247™	SuperSOT™-6
ActiveArray™	FAST®	MICROCOUPLER™	PowerTrench®	SuperSOT™-8
Bottomless™	FASTr™	MicroFET™	QFET®	SyncFET™
CoolFET™	FRFET™	MicroPak™	QS™	TinyLogic®
CROSSVOLT™	GlobalOptoisolator™	MICROWIRE™	QT Optoelectronics™	TINYOPTO™
DOMET™	GTO™	MSX™	Quiet Series™	TruTranslation™
EcoSPARK™	HiSeC™	MSXPro™	RapidConfigure™	UHC™
E ² CMOS™	I ² C™	OCX™	RapidConnect™	UltraFET®
EnSigna™	ImpliedDisconnect™	OCXPro™	SILENT SWITCHER®	VCX™
FACT™	ISOPLANAR™	OPTOLOGIC®	SMART START™	
Across the board. Around the world.™	OPTOPLANAR™	SPM™		
The Power Franchise™	PACMAN™	Stealth™		
Programmable Active Droop™	POP™	SuperSOT™-3		

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.