

FDFS2P102

Integrated P-Channel MOSFET and Schottky Diode

General Description

The FDFS2P102 combines the exceptional performance of Fairchild's high cell density MOSFET with a very low forward voltage drop Schottky barrier rectifier in an SO-8 package.



This device is designed specifically as a single package solution for DC to DC converters. It features a fast switching, low gate charge MOSFET with very low on-state resistance. The independently connected Schottky diode allows its use in a variety of DC/DC converter topologies.

Applications

- DC/DC converters
- Load Switch
- Motor Drives

Features

- $-3.3\text{ A}, -20\text{ V}$. $R_{DS(ON)} = 0.125\ \Omega @ V_{GS} = -10\text{ V}$
 $R_{DS(ON)} = 0.200\ \Omega @ V_{GS} = -4.5\text{ V}$.
- $V_F < 0.39\text{ V @ } 1\text{ A } (T_J = 125\text{ }^\circ\text{C})$.
 $V_F < 0.47\text{ V @ } 1\text{ A}$.
 $V_F < 0.58\text{ V @ } 2\text{ A}$.
- Schottky and MOSFET incorporated into single power surface mount SO-8 package.
- Electrically independent Schottky and MOSFET pinout for design flexibility.



MOSFET Maximum Ratings T_A=25°C unless otherwise noted

Symbol	Parameter	Ratings	Units
V _{DSS}	Drain-Source Voltage	-20	V
V _{GSS}	Gate-Source Voltage	±20	V
I _D	Drain Current - Continuous (Note 1a)	-3.3	A
	- Pulsed	-20	
P _D	Power Dissipation for Dual Operation	2	W
	Power Dissipation for Single Operation (Note 1a)	1.6	
	(Note 1b)	1	
	(Note 1c)	0.9	
T _J , T _{STG}	Operating and Storage Temperature Range	-55 to +150	°C

Schottky Diode Maximum Ratings T_A=25°C unless otherwise noted

V _{RRM}	Repetitive Peak Reverse Voltage	20	V
I _O	Average Forward Current (Note 1a)	1	A

Package Marking and Ordering Information

Device Marking	Device	Reel Size	Tape Width	Quantity
FDFS2P102	FDFS2P102	13	12mm	2500 units

Electrical Characteristics T_A = 25 C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
--------	-----------	-----------------	-----	-----	-----	-------

Off Characteristics

BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0 V, I _D = -250 μA	-20			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = -16 V, V _{GS} = 0 V			-1	μA
		T _J = 55°C			-10	
I _{GSSF}	Gate-Body Forward Leakage	V _{GS} = 20 V, V _{DS} = 0 V			100	nA
I _{GSSR}	Gate-Body Reverse Leakage	V _{GS} = -20 V, V _{DS} = 0 V			-100	nA

On Characteristics (Note 2)

V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = -250 μA	-1	-1.4	-2	V
R _{DS(on)}	Static Drain-Source On-Resistance	V _{GS} = -10 V, I _D = -3.3 A		0.100	0.125	Ω
		V _{GS} = -4.5 V, I _D = -2.5 A		0.167	0.2	
I _{D(on)}	On-State Drain Current	V _{GS} = -10 V, V _{DS} = -5 V	-10			A
g _{FS}	Forward Transconductance	V _{DS} = -10 V, I _D = -3.3 A		5		S

Dynamic Characteristics

C _{ISS}	Input Capacitance	V _{DS} = -10 V, V _{GS} = 0 V, f = 1.0 MHz		270		pF
C _{OSS}	Output Capacitance			150		pF
C _{RSS}	Reverse Transfer Capacitance			45		pF

Switching Characteristics (Note 2)

t _{d(on)}	Turn-On Delay Time	V _{DD} = -15 V, I _D = -1 A, V _{GS} = -10 V, R _{GEN} = 6 Ω		8	16	ns
t _r	Turn-On Rise Time			7	14	ns
t _{d(off)}	Turn-Off Delay Time			17	27	ns
t _f	Turn-Off Fall Time			10	1.8	ns
Q _g	Total Gate Charge	V _{DS} = -5 V, I _D = -3.3 A, V _{GS} = -10 V		7	10	nC

Drain-Source Diode Characteristics and Maximum Ratings

I _S	Maximum Continuous Drain-Source Diode Forward Current				-1.3	A
V _{SD}	Drain-Source Diode Forward Voltage	V _{GS} = 0 V, I _S = -1.3 A <small>(Note 2)</small>		-0.8	-1.2	V

Schottky Diode Characteristics


I _R	Reverse Leakage	V _R = 20 V	T _J = 25°C		250	μA
			T _J = 125°C		18	mA
V _F	Forward Voltage	I _F = 1 A	T _J = 25°C		0.47	V
			T _J = 125°C		0.39	
		I _F = 2 A	T _J = 25°C		0.58	
			T _J = 125°C		0.53	

Thermal Characteristics


R _{JA}	Thermal Resistance, Junction-to-Ambient	<small>(Note 1a)</small>	78		
R _{JC}	Thermal Resistance, Junction-to-Case	<small>(Note 1)</small>	40		

Notes:


1: R_{θJA} is the sum of the junction-to-case and case-to-ambient resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. R_{θJC} is guaranteed by design while R_{θCA} is determined by the user's board design.



a) 50° C/W when mounted on a 1 in² pad of 2 oz. copper.



b) 105° C/W when mounted on a 0.04 in² pad of 2 oz. copper.



c) 125° C/W when mounted on a minimum pad.

Scale 1 : 1 on letter size paper

2: Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%

Typical Characteristics




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

Typical Characteristics (continued)




Figure 7. Gate-Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Schottky Diode Forward Voltage.




Figure 10. Schottky Diode Reverse Current.




Figure 11. Transient Thermal Response Curve.

Thermal characterization performed using the conditions described in Note 1c. Transient thermal response will change depending on the circuit board design.

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE ^x TM	FAST ^r TM	QFET TM	VCX TM
Bottomless TM	GlobalOptoisolator TM	QS TM	
CoolFET TM	GTO TM	QT Optoelectronics TM	
CROSSVOLT TM	HiSeC TM	Quiet Series TM	
DOME TM	ISOPLANAR TM	SuperSOT TM -3	
E ² CMOS TM	MICROWIRE TM	SuperSOT TM -6	
EnSigna TM	OPTOLOGIC TM	SuperSOT TM -8	
FACT TM	OPTOPLANAR TM	SyncFET TM	
FACT Quiet Series TM	POP TM	TinyLogic TM	
FAST [®]	PowerTrench [®]	UHC TM	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.