FAN5350 Evaluation Board User Manual



FAN5350 Evaluation Board User Manual

- 3MHz Fixed Frequency Operation
- 16µA Typical Quiescent Current
- Best-in-Class Load Transient
- Up to 600mA Output Current
- 2.7V to 5.5V Input Voltage Range
- 1.82V Fixed Output Voltage
- Synchronous Operation
- Pulse Skip and Power Save Mode
- 6-lead 3x3mm MLP and 5-bump 1x1.37mm WLCSP Packages

Description:

The FAN5350 Evaluation Board is a compact circuit including the FAN5350 MPX or FAN5350 UCX, a 1 μ H inductor and one small 4.7 μ F input and output capacitor. The FAN5350 demo board is a completely assembled and tested surface mount board, providing easy probe access points to all inputs and outputs so that electrical characteristics and waveforms can be easily measured.



Figure 1: FAN5350 MPX



Figure 2: FAN5350 UCX





Figure 4: WLCSP Schematic Diagram

Where To Begin:

- 1: Connect V_{IN} (2.7 to 5.5V) and GND (0V).
- 2: Use jumper JP1 to select "ON" and "OFF" modes.
- **3:** Verify that the output voltage V_{OUT}, remains constant at 1.82V for varying input voltages and the load current
- **4:** To measure the supply current in non-switching condition, the FB pin has to be forced with an external voltage higher than V_{OUT} nominal. $V_{FB} = 2V$ is a good choice. To measure the supply current in switching condition, the digital current meter readings should be averaged until a stable value is displayed.
- 5: Observe that in OFF mode (EN connected to GND) the supply current drops below 1µA. A typical value at room temperature is ~50nA provided that there is no leakage current through the PCB. Please ensure the PCB surface is very clean when performing this measurement.





Figure 4: WLCSP PCB Layout

Table 1: WLCSP Bill of Materials

Description	Qty	Ref.	Vendor	Part Number
Inductor 1.3uH, 1.2A, 90mohm	1	L1	FDK	MIPSA2520D1R0
Capacitor 4.7uF, 10%, 6.3V, X5R,	2	CIN,COUT	MURATA	GRM39 X5R 475K
0603				6.3
Hardware Connector Header .1 SINGLE STR 36POS	7	Vin,Vout,GND, ON/OFF(JP1)	Digi-Key	\$1011-36-ND
IC DC/DC Regulator in CSP, 5 bumps	1	U1	Fairchild	FAN5350UC
Load Resistor	1	Rload	Any	
Hardware, SHUNT, PHBR 15 AU	1	ON, PWM	DIGI-KEY	A26227-ND

Table 2: MLP Bill of Materials

Description	Qty	Ref.	Vendor	Part Number
Inductor 1.3uH, 1.2A, 90mohm	1	L1	FDK	MIPSA2520D1R0
Capacitor 4.7uF, 10%, 6.3V, X5R,	2	CIN,COUT	MURATA	GRM39 X5R 475K
0603				6.3
Hardware Connector Header .1	14	Vin,Vout,GND,	Digi-Key	S1011-36-ND
SINGLE STR 36POS		LD, ON/OFF(JP1)		
IC DC/DC Regulator in MLP, 6 pin	1	U1	Fairchild	FAN5350MPX
Hardware, SHUNT, PHBR 15 AU	1	ON, PWM	DIGI-KEY	A26227-ND

Table 3: Ordering Information

Product Number	Pb-Free	Operating Temperature Range	Package Type
FAN5350UCX	Yes	-40°C to 85°C	5-bump WLCSP 1x1.37mm
FAN5350MPX	Yes	-40°C to 85°C	6-pin MLP 3x3mm