


14mm (0.56 inch) Four Digit MULTIPLEX CLOCK STICK DISPLAY

Bright Red MSQC6112C, MSQC6142C
High Efficiency Red MSQC6912C, MSQC6942C
Green MSQC6412C, MSQC6442C

PACKAGE DIMENSIONS



Notes:

- Dimensions are in mm (inches)
- All Pins 0.5 (0.020) Diameter
- Tolerances are $\pm 0.25\text{mm}$ (0.010") unless otherwise stated.

Features

- Bright Bold Segments
- Common Anode/Cathode
- Low Power Consumption
- Low Current Capability
- High Performance
- High Reliability

Applications

- Appliances
- Automotive
- Instrumentation
- Process Control

MODELS AVAILABLE

Part Number	Colour	Description
MSQC6112C	Bright Red	Clock Display, Common Anode, gray face, neutral segments
MSQC6142C	Bright Red	Clock Display, Common Cathode, gray face, neutral segments
MSQC6412C	Green	Clock Display, Common Anode, gray face, green segments
MSQC6442C	Green	Clock Display, Common Cathode, gray face, green segments
MSQC6912C	H.E.R	Clock Display, Common Anode, gray face, neutral segments
MSQC6942C	H.E.R.	Clock Display, Common Cathode, gray face, neutral segments

(For other colour options, contact your local area Sales Manager)

**BRIGHT RED MSQC6112C, MSQC6142C
HIGH EFFICIENCY RED MSQC6912C, MSQC6942C
GREEN MSQC6412C, MSQC6442C**

ABSOLUTE MAXIMUM RATINGS⁽¹⁾ (T_A = 25°C, unless otherwise specified)

Part Number Parameter	MSQC6112C MSQC6142C	MSQC6412C MSQC6442C	MSQC6912C MSQC6942C	Units
Continuous Forward Current (each segment)	15	25	25	mA
Peak Forward Current (F = 10KHz, D/F = 1/10)	60	90	90	mA
Power Dissipation (P _D)	40	70	70	mW
*Derate Linearly from 25°C	0.17	0.33	0.33	mW
Reverse Voltage per Die	5 Volts			
Operating and Storage Temperature Range	-40°C to +85°C			
Lead soldering time (1/16 inch from standoff)	5 seconds @ 230°C			

ELECTRO-OPTICAL CHARACTERISTICS⁽¹⁾ (T_A = 25°C, unless otherwise specified)

Part Number Parameter	MSQC6112C MSQC6142C	MSQC6412C MSQC6442C	MSQC6912C MSQC6942C	Units	Test Condition
Luminous intensity ⁽²⁾ (I _V)					
Minimum (Standard Current)	300	800	800	μcd	I _F = 10mA
Typical (Standard Current)	700	2400	2000	μcd	I _F = 10mA
Minimum (Low Current)	Not Available				
Typical (Low Current)	Not Available				
Forward Voltage (V _F)					
Typical (Standard Current)	2.10	2.10	2.00	V	I _F = 20mA
Maximum (Standard Current)	2.80	2.80	2.80	V	I _F = 20mA
Typical (Low Current)	Not Available				
Maximum (Low Current)	Not Available				
Peak Wavelength	695	570	635	nm	I _F = 20mA
Dominant Wavelength	Not Available				
Spectral Line 1/2 Width	90	30	45	nm	I _F = 10mA
Reverse B ⁽³⁾ . Voltage (V _R)	5	5	5	V	I _R = 100uA

NOTES:


(1) Data per individual LED element

(2) Luminous intensity (ucd) = average light output per segment


(3) B = breakdown

BRIGHT RED MSQC6112C, MSQC6142C
HIGH EFFICIENCY RED MSQC6912C, MSQC6942C
GREEN MSQC6412C, MSQC6442C

PIN ORIENTATION, SEGMENT IDENTIFICATION, AND PRODUCT MARKING



SCHEMATICS



BRIGHT RED MSQC6112C, MSQC6142C HIGH EFFICIENCY RED MSQC6912C, MSQC6942C GREEN MSQC6412C, MSQC6442C

GRAPHICAL DATA Bright Red ($T_A = 25^\circ\text{C}$, unless otherwise specified)




Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 Spectral Response




Fig. 3 Relative Luminous Intensity vs. Forward Current




Fig. 5 Luminous Intensity vs. Duty Cycle




Fig. 4 Maximum Allowable DC Current per Segment vs. a Function of Ambient Temperature




Fig. 6 Max Peak Current vs. Duty Cycle % (Refresh Rate $f=1\text{ KHz}$)

BRIGHT RED MSQC6112C, MSQC6142C
HIGH EFFICIENCY RED MSQC6912C, MSQC6942C
GREEN MSQC6412C, MSQC6442C

GRAPHICAL DATA Green ($T_A = 25^\circ\text{C}$, unless otherwise specified)




Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 Spectral Response




Fig. 3 Relative Luminous Intensity vs. Forward Current




Fig. 5 Luminous Intensity vs. Duty Cycle




Fig. 4 Maximum Allowable DC Current per Segment vs. a Function of Ambient Temperature




Fig. 6 Max Peak Current vs. Duty Cycle % (Refresh Rate $f = 1\text{ KHz}$)

**BRIGHT RED MSQC6112C, MSQC6142C
HIGH EFFICIENCY RED MSQC6912C, MSQC6942C
GREEN MSQC6412C, MSQC6442C**

GRAPHICAL DATA High Efficiency Red ($T_A = 25^\circ\text{C}$, unless otherwise specified)




Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 Spectral Response




Fig. 3 Relative Luminous Intensity vs. Forward Current




Fig. 5 Luminous Intensity vs. Duty Cycle




Fig. 4 Maximum Allowable DC Current per Segment vs. a Function of Ambient Temperature




Fig. 6 Max Peak Current vs. Duty Cycle % (Refresh Rate $f=1\text{ KHz}$)

**BRIGHT RED MSQC6112C, MSQC6142C
HIGH EFFICIENCY RED MSQC6912C, MSQC6942C
GREEN MSQC6412C, MSQC6442C**

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.