

XPFM200A+ Medical Power Supply



SPECIFICATIONS:

Ac Input

90-264 Vac, 47-63 Hz single phase.

Input Current

Maximum input current at minimum input voltage and full load is 3.5 A. Active Power Factor Correction circuitry assures compliance with IEC1000-3-2, Class A.

Inrush Current

Inrush is limited by internal thermistors. The inrush at 240 Vac, averaged over the first ac half-cycle under cold start conditions will not exceed 37 A. Worst case current under hot start conditions will be 60 Amps.

Input Protection

Internal ac fuse provided on all units. The fuse is designed to blow only if a catastrophic failure occurs in the unit. The fuse does not blow on unsustained overload or short circuit.

Efficiency

75% typical at full rated load, nominal input voltage, depending on load distribution.

Output Power

Continuous output power 200 W.

Overload Protection

Fully protected against short circuit and output overload. Short circuit protection is cycling type power limit on V1, 2 & 3; thermal foldback type on V4, 5, 6. Power limit factory set to cycle outputs off at 240 W typical. Recovery after removal of fault is automatic.

Over Voltage Protection

Built in on V1, 2 and 6 with firing point set per Table 1. OVP firing shuts down power supply.

Voltage Adjustment

Factory set to specified voltage. Potentiometer on V1 not considered user accessible.

No Load Turn-On/Standby

A minimum load of 1 A on V2 is required for proper regulation. If not met, no degradation of reliability will occur.

Output Regulation

Regulation for all outputs is the maximum deviation from initial set point under all line and load conditions. Initial set tolerance is measured with all outputs at 50 % of full rated load.

FEATURES:

- Medical version of ATX200 power supply
- Approved to IEC601-1 and UL2601
- Includes power factor correction to IEC1000-3-2
- Conducted emissions to CISPR11 class B/IEC601-1-2
- CE marked to LVD

Remote Sense

Provided as a standard feature on V2 (+) lead of all models. Capable of compensating for 0.25 V total of cabling losses in output voltages.

Output Noise

0.5% RMS, 1% Pk-Pk, 20 MHz Bandwidth, differential mode. Measured using a differential noise probe. Probe should be placed directly across the power supply output terminals terminated with a 1uF low Z capacitor.

Transient Response

All outputs stay within their specified regulation limits with a 20% load change. $\Delta i / \Delta t < 0.2 \text{ A} / \mu\text{s}$.

Hold-Up Time

25 ms total from loss of ac input at full load until loss of regulation.

Inhibit

Inhibit signal is pulled to the dc output common to inhibit V1 - 5 voltages. ($V = < 0.4\text{V}$, sink $> 1.5\text{mA}$)

Power Good

TTL / CMOS compatible output rises high 100 to 400 ms after V2 reaches regulation and should assure that sufficient energy is stored in the input section to provide normal power fail / shutdown.

Temperature Coefficient

0.03% / °C typical on all outputs.

Turn-On Time

Less than 2 s at 120 Vac 25°C

Storage

-40 to +85 °C.

Leakage Current

90µA under normal conditions (120 Vac @ 60 Hz). Maximum under single-fault conditions (264 Vac @ 50 Hz) is 300 µA.

EMI/EMC Compliance

All models include built-in EMI filtering to meet the following emissions requirements:

EMI SPECIFICATIONS	COMPLIANCE LEVEL
Conducted Emissions	EN55011, Class B; FCC Class B
Static Discharge	EN61000-4-2, 6 kV contact 8 kV air
RF Field Susceptibility	EN61000-4-3, 3V/meter
Fast Transients / Bursts	EN61000-4-4, 2 kV, 5 kHz
Surge Susceptibility	EN61000-4-5, 1 kV diff., 2 kV com.
Conducted RF Susceptibility	EN61000-4-6, 3V
Voltage Sags & Surges	EN61000-4-11

Safety Agency

All models are certified to be in compliance with the applicable requirements of UL2601-1, CSA-C22.2 No. 601.1, IEC601-1/60601-1.

