


Omnimate Range - 7.50 mm Pitch



Socket blocks BLZF 7.50/180



Technical data	VDE	UL	CSA
Rated voltage (V)	500*	300	300
Rated current (A)	16	10	15
Wire size (mm ² /AWG)	1.5	26...12	26...12

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 226

Color



Poles	Type	Part No.	Part No.	Qty.
2	BLZF 7.50/2/180	1717260000	1722940000	100
3	BLZF 7.50/3/180	1717270000	1722950000	100
4	BLZF 7.50/4/180	1717280000	1722960000	100
5	BLZF 7.50/5/180	1717290000	1722970000	50
6	BLZF 7.50/6/180	1718570000	1722980000	50
7	BLZF 7.50/7/180	1717300000	1722990000	50
8	BLZF 7.50/8/180	1717310000	1723000000	50
9	BLZF 7.50/9/180	1718580000	1723010000	50
10	BLZF 7.50/10/180	1718590000	1723020000	50
11	BLZF 7.50/11/180	1718600000	1723030000	50
12	BLZF 7.50/12/180	1718610000	1723040000	50

Accessories	Page
Mounting	–
Marking	190
Coding	193
Miscellaneous	201, 202